# WATERWORKS

EALS02 **EASTON** 

Easton Classic Low Profile Three Hole Deck Mounted Lavatory Faucet with Metal Lever Handles



SHOWN IN EASTON CLASSIC LOW PROFILE THREE HOLE DECK MOUNTED LAVATORY FAUCET WITH METAL LEVER

# **INSPIRATION**

Drawing on Edwardian style, Easton is the most extensive Waterworks family; a range of moods and a selection of products from fittings to furniture.

#### **TECHNICAL DETAILS**

ADA Compliance: Yes

Adjustable versus Fixed Spray: Fixed Spray

Deck Thickness Maximum: 32 mm

Deck Thickness Minimum: 0 mm

Drain Assembly Materials: Brass Drain Depth Maximum: 35 mm

Drain Hole Diameter: 44 mm

Drain Style: Pop-up

Escutcheon Primary Material: Brass

Fittings Hole Diameter: 35 mm

Handle Spread Maximum: 305 mm Handle Spread Minimum: 203 mm

Handle Turn Angle: Quarter Turn

Index Color / Finish and Material: White Porcelain

Depth / Width: 229 mm

Drain Depth Minimum: 44 mm

Height: 89 mm

Index Marking: Hot/Cold

Inlet Connection Size: 1/2"

Inlet Connection Type: Male with supply nut

Inlet Supply Spread Maximum: 305 mm

Inlet Supply Spread Minimum: 203 mm

Installation Type: Deck Mounted

Length: 406 mm

Number of Handles: Two

Number of Holes: Three Hole

Primary Material: Brass

Restricted Maximum Flow Rate: 4.5 liters/min

Spout Swivel: N

Suggested Application: Bath

Valve Material: Ceramic

Water Pressure Maximum: 6.0 bar

Water Pressure Minimum: 1.5 bar

Water Pressure Recommended: 3.0 bar

## **CODES & STANDARDS**

Code # EALS02: ASME A112.18.1, CSA B125, NSF, CEC, IAPMO, State of MA

## **PRODUCT FEATURES**

Brass metal is used for all trim and valve components

The manufacturing process encompasses casting, turning, forging, hand-fitting and hand polishing.

Easton is our most comprehensive fittings family.

Easton has a clean-lined utilitarian profile, with a slightly elongated spout.

Available in 1.2gpm (4.5L/min) flow rate

## **CERTIFICATIONS**



EASTON EALS02

Easton Classic Low Profile Three Hole Deck Mounted Lavatory Faucet with Metal Lever Handles

