BOULEVARD BD87TF

Boulevard Low Profile Concealed Tub Filler With Handshower and Metal Cross Handles



SHOWN IN BOULEVARD LOW PROFILE CONCEALED TUB FILLER WITH HANDSHOWER AND METAL CROSS HANDLES| BDTF87

TECHNICAL DETAILS

ADA Compliance: No

Adjustable versus Fixed Spray: Fixed Spray Deck Thickness Maximum: 43 mm Deck Thickness Minimum: 0 mm Diameter of Head: 51 mm **Escutcheon Primary Material: Brass** Fittings Hole Diameter: 35 mm Flow Restriction Options: 2.0, 1.75, 1.5, 0.92 Handle Spread Maximum: 305 mm Handle Spread Minimum: 254 mm Handle Turn Angle: Quarter Turn Handshower / Spray Hose Length: 2.0 m Depth / Width: 279 mm Height: 152 mm Index Marking: Blank Inlet Connection Size: 3/4" Inlet Connection Type: Male G/BSPP Inlet Supply Spread Maximum: 305 mm Inlet Supply Spread Minimum: 254 mm Installation Type: Deck Mounted Integrated Diverter: N Length: 330 mm Number of Handles: Two Number of Holes: Four Hole Primary Material: Brass Restricted Maximum Flow Rate: 9.5 liters/min Spout Reach: 9" Spout Swivel: N Suggested Application: Bath Valve Material: ceramic Water Pressure Maximum: 5.5 bar Water Pressure Minimum: 1.5 bar Water Pressure Recommended: 3.0 bar

INSPIRATION

Inspiration from 1930s objects evokes extravagance: a strong silhouette, lavish scale and elegant decoration. Machine and artisan hands yield crisp details and curves.

CODES & STANDARDS

Code #: ASME A112.18.1, CSA B125, IAPMO, State of MA

PRODUCT FEATURES

Brass metal is used for all trim and valve components.

The manufacturing process encompasses casting, turning, forging, hand-fitting and hand polishing.

Solidly sized and generous in scale, decorative elements convey a sense of substance. Standard flow rate is 2.5gpm for handshower only. Also available in high efficiency flow options. Contact your sales associate or call 1 (800) 899-6757 for details.

BOULEVARD BD87TF

Boulevard Low Profile Concealed Tub Filler With Handshower and Metal Cross Handles

