

## HENRY

## HNXS20

Henry Exposed Thermostatic Shower System with 8" Shower Head and Metal Cross Handle



SHOWN IN HENRY EXPOSED THERMOSTATIC SHOWER SYSTEM WITH 8" SHOWER HEAD AND METAL CROSS HANDLE

### TECHNICAL DETAILS

Adjustable versus Fixed Spray: Fixed Spray  
 Diameter of Head: 7 3/4"  
 Diameter of Legs / Tubes: 1 1/8"  
 Escutcheon Primary Material: Brass  
 Fittings Hole Diameter: 1 1/8"  
 Flow Restriction Options: 2.5, 2.0, 1.75, 1.5  
 Handle Spread Maximum: 5 11/16"  
 Handle Spread Minimum: 5 11/16"  
 Handle Turn Angle: Quarter Turn  
 Handshower / Spray Hose Length: 59"  
 Inlet Connection Size: 3/4"  
 Inlet Connection Type: Copper Compression  
 Inlet Supply Spread Maximum: 11 5/8"  
 Inlet Supply Spread Minimum: 11 1/8"  
 Installation Type: Wall Mounted  
 Integrated Diverter: N  
 Integrated Spray: N  
 Number of Handles: Two  
 Number of Holes: Two Hole  
 Pivot: Y  
 Primary Material: Brass  
 Suggested Application: Bath  
 Valve Material: Wax Element  
 Water Pressure Maximum: 85.0 psi  
 Water Pressure Minimum: 20.0 psi  
 Water Pressure Recommended: 45.0 psi

### INSPIRATION

Influenced by the connection of industry and art Henry easily transitions between modern, traditional, utilitarian and classic settings.

### PRODUCT FEATURES

Available Late Spring 2018

Features an integrated thermostatic shut-off valve

Stocked in Nickel, Chrome, Unlacquered Brass, and Matte Nickel finishes

Standard flow rate is 2.5gpm (9.5 L/min). Also available in high efficient flow options. Contact your sales associate or call 1 (800) 899-6757 for details.



# WATERWORKS

## HENRY

## HNXS20

Henry Exposed Thermostatic Shower System with 8" Shower Head and Metal Cross Handle

