HENRY HNLS40

Henry Low Profile One Hole Deck Mounted Lavatory Faucet with Metal Cross Handle



TECHNICAL DETAILS

ADA Compliance: Yes

Adjustable versus Fixed Spray: Fixed Spray

Deck Thickness Maximum: 1 1/4" Deck Thickness Minimum: 0"

Drain Depth Maximum: 2 5/8" Drain Hole Diameter: 1 3/4"

Escutcheon Primary Material: Brass

Fittings Hole Diameter: 1 3/8"

Flow Restriction Options: 1.0 , 1.2 , 1.5 , 1.75, 2.2

Handle Turn Angle: Half Turn Depth / Width: 7 3/16" Drain Depth Minimum: 3/8"

Height: 4 7/16"

Inlet Connection Size: 3/8"

Inlet Connection Type: Compression Connector Hoses

Installation Type: Deck Mounted

Integrated Diverter: N

Integrated Spray: N Length: 2 7/8"

Number of Handles: One

Number of Holes: One Hole

Primary Material: Brass

Spout Swivel: N

Spray Included in Unit: N

Suggested Application: Bath Valve Material: Ceramic

Water Pressure Maximum: 85.0 psi

Water Pressure Minimum: 20.0 psi

Water Pressure Recommended: 45.0 psi

L SHOWN IN HENRY LOW PROFILE ONE HOLE DECK MOUNTED LAVATORY FAUCET WITH METAL CROSS HANDLE| HNLS40

INSPIRATION

Influenced by the connection of industry and art Henry easily transitions between modern, traditional, utilitarian and classic settings.

CODES & STANDARDS

Code # HNLS40X: Complies with ASME A112.18.1/CSA B125.1, ASME A112.18.2 / CSA B125.2, NSF, CEC 61, ADA and 0.25% Weighted Average Lead Content. Certified with IAPMO, cUPC, NSF, CEC and State of MA.

PRODUCT FEATURES

The manufacturing process encompasses casting, turning, forging, hand-fitting and hand polishing. Brass material is used for component.

Standard flow rate is 2.2gpm (8.3 L/min) and State of California requires 1.2gpm(4.5 L/min). Also available in other flow options. Contact a sales associate for details.

HENRY HNLS40

Henry Low Profile One Hole Deck Mounted Lavatory Faucet with Metal Cross Handle

