## WATERWORKS

ELSA ELLS63

Elsa Low Profile Three Hole Deck Mounted Lavatory Faucet with Metal Cross Handles



#### **TECHNICAL DETAILS**

Adjustable versus Fixed Spray: Fixed Spray Deck Thickness Maximum: 1 13/16" Deck Thickness Minimum: 0" **Drain Assembly Materials: Brass** Drain Depth Maximum: 1 3/4" Drain Hole Diameter: 1 3/4" Drain Style: Pop-up Escutcheon Primary Material: brass Fittings Hole Diameter: 1 1/4" Flow Restriction Options: 1.75, 1.5, 1.0 Handle Spread Maximum: 12" Handle Spread Minimum: 8" Handle Turn Angle: Quarter Turn Depth / Width: 8" Drain Depth Minimum: 1 3/8" Height: 3 1/2" Inlet Connection Size: 1/2" Inlet Connection Type: Male with Supply Nut Inlet Supply Spread Maximum: 12" Inlet Supply Spread Minimum: 8" Length: 11 1/2" Number of Holes: Three Hole

Primary Material: Brass Restricted Maximum Flow Rate: 2.2 gpm Spout Swivel: N Suggested Application: Bath Valve Material: Ceramic Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi

Water Pressure Recommended: 45.0 psi

SHOWN IN CHROME

### **INSPIRATION**

An updated 1930's design that is curvaceous and bold; Elsa conveys charm, warmth and a touch of whimsy.

### **CODES & STANDARDS**

Code # ELLS63: Certified with NSF, IAPMO & State of MA. Complies with ASME A112.18.1, CSA B125, ASME A112.18.2 / CSA B125.2, ANSI 117.1 ADA, & ASTM E 1621-05.

### **PRODUCT FEATURES**

Brass material is used for all trim and valve component parts.

 $The \ manufacturing \ process \~A \boxtimes \^A \ encompasses \~A \boxtimes \^A \ casting, turning, hand-fitting \ and \ hand \ polishing.$ 

The smooth, sculptural contours and simplified linear detail ensure that Elsa will be comfortable and welcomed in any bathroom.

Standard flow rate is 2.2gpm (8.3 L/min). Also available in high efficient flow options. Contact your sales associate or call 1 (800) 899-6757 for details.

### **CERTIFICATIONS**



# ELSA ELLS63

Elsa Low Profile Three Hole Deck Mounted Lavatory Faucet with Metal Cross Handles

