

## JULIA

## JUKM43

Julia Two Hole Bridge Articulated Kitchen Faucet, Metal Lever Handles and Spray



SHOWN IN JULIA TWO HOLE BRIDGE ARTICULATED KITCHEN FAUCET, METAL LEVER HANDLES AND SPRAY| JUKM43

### TECHNICAL DETAILS

Deck Thickness Maximum: 1 1/2"  
Deck Thickness Minimum: 1/4"  
Fittings Hole Diameter: 1 1/4"  
Handle Spread Maximum: 7 7/8"  
Handle Spread Minimum: 7 7/8"  
Handle Turn Angle: Quarter Turn  
Handshower / Spray Hose Length: 49"  
Depth / Width: 21 1/4"  
Height: 10 15/16"  
Inlet Connection Size: 1/2"  
Inlet Connection Type: Male with supply nut  
Inlet Supply Spread Maximum: 7 7/8"  
Inlet Supply Spread Minimum: 7 7/8"  
Primary Material: Brass  
Restricted Maximum Flow Rate: 2.2 gpm  
Spout Swivel: Y  
Spray Included in Unit: N  
Suggested Application: Bar, Kitchen, Laundry  
Valve Material: Ceramic  
Water Pressure Maximum: 85.0 psi  
Water Pressure Minimum: 20.0 psi  
Water Pressure Recommended: 45.0 psi

### INSPIRATION

An interpretation of 1920s French country, Julia speaks to decoration and intricate design displayed through beautifully composed turnings. These details embody the robust, signature high profile spout enabling Julia to transition fluidly from informal to formal environments.

### CODES & STANDARDS

Code # JUKM43: CEC

### PRODUCT FEATURES

Articulating Spout

Smooth folding action for easy storage or far reach into the sink

Quarter turn ceramic cartridge

Provided with Side Spray and Control Valve

Standard flow rate is 2.2gpm (8.3 L/min) and State of California requires a maximum of 1.8gpm(6.8 L/min). Also available in other flow options. Contact a sales associate for details.

# WATERWORKS

## JULIA

## JUKM43

Julia Two Hole Bridge Articulated Kitchen Faucet, Metal Lever  
Handles and Spray

