WATERWORKS

AMELIE AMXT05

Amelie Exposed Tub Filler With Handshower and Cross Handles



SHOWN IN AMELIE EXPOSED TUB FILLER WITH HANDSHOWER AND CROSS HANDLES AMXT05

TECHNICAL DETAILS

ADA Compliance: No

Adjustable versus Fixed Spray: Fixed Spray

Diameter of Head: 7 5/8"

Escutcheon Primary Material: brass

Flow Restriction Options: 2.0, 1.75, 1.5, 0.92

Handle Spread Maximum: 3"

Handle Spread Minimum: 3"

Handle Turn Angle: Quarter Turn

Handshower / Spray Hose Length: 59"

Index Color / Finish and Material: White Porcelain

Depth / Width: 9 1/4"

Height: 15"

Index Marking: Hot/Cold

Inlet Connection Size: 3/4"

Inlet Connection Type: Union Nut

Inlet Supply Spread Maximum: 7 5/8"

Inlet Supply Spread Minimum: 7 5/8"

Installation Type: Wall or deck mounted

Integrated Diverter: Y

Length: 10 1/4"

Number of Handles: Three

Pivot: N

Primary Material: Brass

Restricted Maximum Flow Rate: 2.5 gpm

Spout Swivel: N

Suggested Application: Bath

Valve Material: Ceramic

Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi

Water Pressure Recommended: 45.0 psi

INSPIRATION

The ultimate in decorative, luxurious fittings with no apologies for its lack of restraint. Amelie offers curves, moldings and detailing combined to create an over-the-top effect which is luxurious, Old World and elegant.

CODES & STANDARDS

Code # AMTU05: ASME A112.18.1, CSA B125, IAPMO, State of MA

PRODUCT FEATURES

Brass material is used for all trim and valve component parts.

The manufacturing process encompasses casting, turning, forging, hand-fitting and hand polishing. Standard flow rate is 2.5gpm for handshower only. Also available in high efficient flow options. Contact your sales associate or call 1 (800) 899-6757 for details.









AMELIE AMXT05

Amelie Exposed Tub Filler With Handshower and Cross Handles

