WATERWORKS

AMELIE AMTF10

Amelie Deck Mounted High Profile Concealed Tub Filler with White Porcelain Handshower and Metal Lever Handles



SHOWN IN NICKEL WITH LEVER HANDLES

The ultimate in decorative, luxurious fittings with no apologies for its lack of restraint. Amelie offers curves, moldings and detailing combined to create an over-the-top effect which is luxurious, Old World and elegant.

INSPIRATION

CODES & STANDARDS

TECHNICAL DETAILS

Escutcheon Primary Material: Brass Fittings Hole Diameter: 1 3/8"

Handle Spread Maximum: 12"
Handle Spread Minimum: 10"
Handle Turn Angle: Quarter Turn
Handshower / Spray Hose Length: 79"
Index Color / Finish and Material: White Porcelain

Depth / Width: 11 1/2" Height: 10"

Pivot: N

Index Marking: Hot/Cold Inlet Connection Size: 3/4"

Primary Material: Brass

Suggested Application: Bath Valve Material: Ceramic Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

Spout Reach: 9 1/4" Spout Swivel: N

Adjustable versus Fixed Spray: Fixed Spray Deck Thickness Maximum: 1 1/2" Deck Thickness Minimum: 0" Diameter of Head: 3"

Flow Restriction Options: 2.0, 1.75, 1.5, 0.92

Inlet Connection Type: Male NPT Adapter Inlet Supply Spread Maximum: 12" Inlet Supply Spread Minimum: 10" Installation Type: Deck Mounted Integrated Diverter: N Length: 17 1/4" Number of Handles: Two Number of Holes: Four Hole

Restricted Maximum Flow Rate: 2.5 gpm

ADA Compliance: No

Code # AMTU10: ASME A112.18.1, ASSE 1014, IAPMO, State of MA $\,$

PRODUCT FEATURES

Brass material is used for all trim and valve component parts.

The manufacturing process encompasses casting, turning, forging, hand-fitting and hand polishing.

Standard flow rate is 2.5gpm for handshower only. Also available in high efficient flow options. Contact your sales associate or call 1 (800) 899-6757 for details.

CERTIFICATIONS





AMELIE AMTF10

Amelie Deck Mounted High Profile Concealed Tub Filler with White Porcelain Handshower and Metal Lever Handles

