HENRY HNXT40

Henry Exposed Deck Mounted Tub Filler With Handshower and Metal Cross Handles



SHOWN IN HENRY EXPOSED DECK MOUNTED TUB FILLER WITH HANDSHOWER AND METAL CROSS HANDLES | HNXT40

TECHNICAL DETAILS

ADA Compliance: Yes

Adjustable Versus Fixed Spray: Fixed Spray

Deck Thickness Maximum: 2 1/2" Deck Thickness Minimum: 0" Depth/Width: 10 1/8" Diameter Of Head: 1 7/8"

Escutcheon Primary Material: Brass Fittings Hole Diameter: 1 1/8"

Flow Restriction Options: 2.5, 2.0, 1.75, 1.5, 0.92

Handle Spread Maximum: 8" Handle Spread Minimum: 8" Handle Turn Angle: Quarter Turn Handshower Spray Hose Length: 59"

Height: 16 11/16'

Inlet Connection Size: 3/4"

Inlet Connection Type: Copper Sweat Inlet Supply Spread Maximum: 8" Inlet Supply Spread Minimum: 8" Installation Type: Deck Mounted

Integrated Diverter: N Integrated Spray: N Number Of Handles: Two Number Of Holes: Two Hole

Pivot: N

Primary Material: Brass Spout Swivel: N Spray Included In Unit: N Suggested Application: Bath Valve Material: Ceramic

Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

INSPIRATION

Influenced by the connection of industry and art Henry easily transitions between modern, traditional, utilitarian and classic settings.

CODES & STANDARDS

Code # HNTU40X: Complies with ASME A112.18.1/CSA B125.1, cUPC, and ADA. Certified with IAPMO, CEC, DOE, State of MA, and WRAS.

PRODUCT FEATURES

The manufacturing process encompasses casting, turning, forging, hand-fitting and hand polishing.

Brass material is used for components.

Includes deck unions

Stocked in 2.5gpm (9.5 L/min) and 1.75gpm (6.6 L/min) for Handshower. State of California requires 1.75gpm (6.6 L/min) to comply with their water conservation requirements. Other flow options are available to order, contact your sales associate or call 1 (800) 899-6757 for details

CERTIFICATIONS







PRODUCT (NOTES)

HENRY HNXT40

Henry Exposed Deck Mounted Tub Filler With Handshower and Metal Cross Handles

