WATERWORKS

HNLS31 **HENRY**

Henry Gooseneck Three Hole Deck Mounted Lavatory Faucet with Teak Cylinders and Metal Lever Handles



TECHNICAL DETAILS

Adjustable versus Fixed Spray: Fixed Spray Deck Thickness Maximum: 1 5/8" Deck Thickness Minimum: 3/16" Drain Depth Maximum: 25/8" Drain Hole Diameter: 1 3/4" Escutcheon Primary Material: Brass Fittings Hole Diameter: 1 1/4" Flow Restriction Options: 1.0, 1.2, 1.5, 1.75, 2.2

Handle Spread Maximum: 12"

Handle Spread Minimum: 8" Handle Turn Angle: Quarter Turn Depth / Width: 7 13/16" Drain Depth Minimum: 3/8" Height: 9"

Inlet Connection Size: 1/2"

Inlet Connection Type: Male with Supply Nut Inlet Supply Spread Maximum: 12" Inlet Supply Spread Minimum: 8" Installation Type: Deck Mounted Integrated Diverter: N Integrated Spray: N Number of Handles: Two Number of Holes: Three Hole

Primary Material: Brass Spout Swivel: N Spray Included in Unit: N Suggested Application: Bath Valve Material: Ceramic

Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

INSPIRATION

Influenced by the connection of industry and art Henry easily transitions between modern, traditional, utilitarian and classic settings.

CODES & STANDARDS

Code # HNLS31X: Complies with ASME A112.18.1/CSA B125.1, ASME A112.18.2 / CSA B125.2, NSF, CEC 61, ADA and 0.25% Weighted Average Lead Content. Certified with IAPMO, cUPC, NSF, CEC and State of MA.

PRODUCT FEATURES

Teak is an organic, natural hardwood originating from Southeast Asia

The manufacturing process encompasses casting, turning, forging, hand-fitting and hand polishing. Standard flow rate is 2.2qpm (8.3 L/min) and State of California requires 1.2qpm(4.5 L/min). Also available in other flow options. Contact a sales associate for details.

CERTIFICATIONS



HENRY HNLS31

Henry Gooseneck Three Hole Deck Mounted Lavatory Faucet with Teak Cylinders and Metal Lever Handles

