WATERWORKS

ATTF37 **ASTORIA**

Astoria Low Profile Concealed Tub Filler With Handshower and Metal Cross Handles



SHOWN IN ASTORIA LOW PROFILE CONCEALED TUB FILLER WITH HANDSHOWER AND METAL CROSS HANDLES ATTF37

TECHNICAL DETAILS

ADA Compliance: No Adjustable versus Fixed Spray: Fixed Spray Deck Thickness Maximum: 1 7/8" Deck Thickness Minimum: 0" Diameter of Head: 2" Escutcheon Primary Material: Brass Fittings Hole Diameter: 1 3/8" Flow Restriction Options: 2.0, 1.75, 1.5, 0.92 Handle Spread Maximum: 12" Handle Spread Minimum: 10"

Handle Turn Angle: Quarter Turn Handshower / Spray Hose Length: 79" Index Color / Finish and Material: White Porcelain

Depth / Width: 10 1/2" Height: 5 1/2"

Index Marking: Hot/Cold Inlet Connection Size: 3/4"

Inlet Connection Type: Male NPT Adapter Inlet Supply Spread Maximum: 12" Inlet Supply Spread Minimum: 10" Installation Type: Deck Mounted Integrated Diverter: N Length: 20"

Number of Handles: Two Number of Holes: Four Hole

Pivot: N Primary Material: Brass

Restricted Maximum Flow Rate: 2.5 gpm Spout Swivel: N

Suggested Application: Bath Valve Material: Ceramic Water Pressure Maximum: 85.0 psi

Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

INSPIRATION

Astoria is dignified tradition. Firmly grounded in the 1930's, the design is an eclectic mix of distinctive geometric profiles, generous scale, and elegant design.

CODES & STANDARDS

Code # JUTU37:

PRODUCT FEATURES

Brass material is used for all trim and valve component parts.

The manufacturing process encompasses casting, turning, hand-fitting and hand polishing.

Standard flow rate is 2.5gpm for handshower only. Also available in high efficient flow options. Contact your sales associate or call 1 (800) 899-6757 for details.









ASTORIA ATTF37

Astoria Low Profile Concealed Tub Filler With Handshower and Metal Cross Handles

