

## HENRY

Henry Metal Lever Handle Thermostatic with Metal Cross Handle Shutoffs Trim

## HNTH30



SHOWN IN HENRY METAL LEVER HANDLE THERMOSTATIC WITH METAL CROSS HANDLE SHUTOFFS TRIM| HNTH30

### TECHNICAL DETAILS

ADA Compliance: Yes  
 Control Valve Rough-in Depth Maximum: 4 1/8"  
 Control Valve Rough-in Depth Minimum: 2 1/8"  
 Diverter Valve Rough-in Depth Maximum: 4 1/8"  
 Diverter Valve Rough-in Depth Minimum: 2 7/8"  
 Escutcheon Primary Material: Brass  
 Fittings Hole Diameter: 5 1/4"  
 Depth / Width: 3 15/16"  
 Height: 16 1/8"  
 Integrated Diverter: N  
 Integrated Spray: N  
 Length: 8 11/16"  
 Number of Handles: Three  
 Pivot: N  
 Primary Material: Brass  
 Spout Swivel: N  
 Spray Included in Unit: N  
 Suggested Application: Bath  
 Water Pressure Maximum: 85.0 psi  
 Water Pressure Minimum: 20.0 psi  
 Water Pressure Recommended: 45.0 psi

### INSPIRATION

Influenced by the connection of industry and art Henry easily transitions between modern, traditional, utilitarian and classic settings.

### CODES & STANDARDS

Code # HNSV30X: Complies with ASME A112.18.1/CSA B125.1 & ANSI A117.1 ADA. Certified with IAPMO, cUPC & State of MA

### PRODUCT FEATURES

The manufacturing process encompasses casting, turning, forging, hand-fitting and hand polishing.

Brass material is used for components

A new unique rough was engineered to house this layout which was based on our TM5 platform.



## HENRY

## HNTH30

Henry Metal Lever Handle Thermostatic with Metal Cross Handle Shutoffs Trim

