

## ETOILE

ETLS66

Etoile Low Profile Two Hole Wall Mounted Lavatory Faucet  
(Straight Spout) with Cross Handles



SHOWN IN ETOILE LOW PROFILE TWO HOLE WALL MOUNTED LAVATORY FAUCET (STRAIGHT SPOUT) WITH CROSS HANDLES | ETLS66

### TECHNICAL DETAILS

ADA Compliance: Yes  
Adjustable Versus Fixed Spray: Fixed Spray  
Depth/Width: 9"  
Drain Assembly Materials: Brass  
Drain Depth Maximum: 2 3/4"  
Drain Depth Minimum: 1"  
Drain Hole Diameter: 1 3/4"  
Drain Style: Lift and Turn  
Escutcheon Primary Material: Brass  
Fittings Hole Diameter: 1 1/4"  
Handle Spread Maximum: 7 7/8"  
Handle Spread Minimum: 7 7/8"  
Handle Turn Angle: Quarter Turn  
Height: 2 7/8"  
Index Color Finish And Material: White Porcelain  
Index Marking: H/C  
Inlet Connection Size: 1/2"  
Inlet Connection Type: Female NPT  
Inlet Supply Spread Maximum: 7 7/8"  
Inlet Supply Spread Minimum: 7 7/8"  
Installation Type: Wall Mounted  
Length: 10 1/4"  
Number Of Handles: Two  
Number Of Holes: Two Hole  
Primary Material: Brass  
Restricted Maximum Flow Rate: 1.2 gpm  
Spout Swivel: N  
Suggested Application: Bath  
Valve Material: Ceramic  
Water Pressure Maximum: 85.0 psi  
Water Pressure Minimum: 20.0 psi  
Water Pressure Recommended: 45.0 psi

### INSPIRATION

Defined elegance. Etoile has a European sophistication with a timeless sense of chic.

### CODES & STANDARDS

Code # ETLS66: Certified with IAPMO, NSF, CEC & State of MA. Complies with ASME A112.18.1 / CSA B125.1, ANSI 61 Sect. 9, ANSI A117.1 ADA, & ASTM E 1621-05.

### PRODUCT FEATURES

- Metal cross handles
- Includes European size lift and turn drain
- Features dew-drop designed cross handles and graceful, elongated curves
- Stocked in Chrome, Nickel, Matte Nickel, and Unlacquered Brass
- Available in 1.2gpm (4.5L/min) flow rate

### CERTIFICATIONS



### PRODUCT (NOTES)

Sold with European style drain; USA style drain sold separately for use with non-Waterworks sinks.

## ETOILE

ETLS66

Etoile Low Profile Two Hole Wall Mounted Lavatory Faucet  
(Straight Spout) with Cross Handles

