

ORLEANS

ORKM02

Orleans One Hole Gooseneck Kitchen Faucet, Metal Lever Handle and Spray



SHOWN IN ORLEANS ONE HOLE GOOSENECK KITCHEN FAUCET, METAL LEVER HANDLE AND SPRAY | ORKM02

TECHNICAL DETAILS

ADA Compliance: Yes
 Adjustable versus Fixed Spray: Fixed Spray
 Deck Thickness Maximum: 1 1/2"
 Deck Thickness Minimum: 0"
 Escutcheon Primary Material: Brass
 Fittings Hole Diameter: 1 3/8"
 Flow Restriction Options: 1.75, 1.5, 1.0
 Handle Turn Angle: Quarter Turn Each Way
 Depth / Width: 9 3/8"
 Height: 13"
 Inlet Connection Size: 3/8"
 Inlet Connection Type: Compression Connector Hoses
 Inlet Supply Spread Maximum: 1/2"
 Inlet Supply Spread Minimum: 1/2"
 Interior / Exterior Application: Interior Only
 Length: 12"
 Number of Handles: One
 Number of Holes: Two Hole
 Primary Material: Brass
 Restricted Maximum Flow Rate: 2.2 gpm
 Spout Swivel: Y
 Spray Included in Unit: Y
 Suggested Application: Bar, Kitchen, Laundry
 Valve Material: Ceramic
 Water Pressure Maximum: 85.0 psi
 Water Pressure Minimum: 20.0 psi
 Water Pressure Recommended: 45.0 psi

INSPIRATION

Our Orleans collection allows for a design continuity throughout the house from urban modern to French country classic English and beyond.

CODES & STANDARDS

Code # ORKM01: ASME A112.18.1 / CSA B125.1, IAPMO, CEC & NSF

PRODUCT FEATURES

A proportioned mixer that offers a small footprint, yet delivers large kitchen amenities. Exceptional control of the flow and temperature for cooks. A slight touch via the elbow, wrist, or back of hand actuates and adjusts the flow of the water.

Lever handle can be positioned on either left or right side by rotating spout 180 degrees.

Standard flow rate is 2.2gpm (8.3 L/min) and State of California requires a maximum of 1.8gpm(6.8 L/min). Also available in other flow options. Contact a sales associate for details.



WATERWORKS

ORLEANS

ORKM02

Orleans One Hole Gooseneck Kitchen Faucet, Metal Lever Handle and Spray

