# WATERWORKS

HENRY HNLS30

Henry Gooseneck Three Hole Deck Mounted Lavatory Faucet with Metal Lever Handles



L Shown in Henry Gooseneck three hole deck mounted lavatory faucet with metal lever handles| HNLS30

## INSPIRATION

Influenced by the connection of industry and art Henry easily transitions between modern, traditional, utilitarian and classic settings.

#### **TECHNICAL DETAILS**

ADA Compliance: Yes

Adjustable versus Fixed Spray: Fixed Spray Deck Thickness Maximum: 41 mm Deck Thickness Minimum: 5 mm Drain Depth Maximum: 67 mm Drain Hole Diameter: 44 mm Escutcheon Primary Material: Brass Fittings Hole Diameter: 32 mm Handle Spread Maximum: 305 mm Handle Spread Minimum: 203 mm Handle Turn Angle: Quarter Turn Depth / Width: 198 mm Drain Depth Minimum: 10 mm Height: 229 mm Inlet Connection Size: 1/2" Inlet Connection Type: Male with Supply Nut Inlet Supply Spread Maximum: 305 mm Inlet Supply Spread Minimum: 203 mm Installation Type: Deck Mounted Integrated Diverter: N Integrated Spray: N Number of Handles: Two Number of Holes: Three Hole Primary Material: Brass Restricted Maximum Flow Rate: 4.5 liters/min Spout Swivel: N Spray Included in Unit: N Suggested Application: Bath Valve Material: Ceramic Water Pressure Maximum: 6.0 bar Water Pressure Minimum: 1.5 bar Water Pressure Recommended: 3.0 bar

#### **CODES & STANDARDS**

Code # HNLS30X: Complies with ASME A112.18.1/CSA B125.1, ASME A112.18.2 / CSA B125.2, NSF, CEC 61, ADA and 0.25% Weighted Average Lead Content. Certified with IAPMO, cUPC, NSF, CEC and State of MA.

### **PRODUCT FEATURES**

Metal lever handles

Includes European size push touch drain

The manufacturing process encompasses casting, turning, forging, hand-fitting and hand polishing.

Stocked in Chrome, Nickel, Matte Nickel, and Unlacquered Brass

Available in 1.2gpm (4.5L/min) flow rate

#### **CERTIFICATIONS**



HENRY HNLS30

Henry Gooseneck Three Hole Deck Mounted Lavatory Faucet with Metal Lever Handles

