WATERWORKS

AERO RETRO RTLS02

Aero Retro Low Profile Three Hole Deck Mounted Lavatory Faucet with Metal Lever Handles



TECHNICAL DETAILS

ADA Compliance: Yes
Adjustable versus Fixed Spray: Fixed Spray
Deck Thickness Maximum: 1 11/16"
Deck Thickness Minimum: 0"
Drain Assembly Materials: Brass
Drain Depth Maximum: 1 3/4"
Drain Hole Diameter: 1 5/8"
Drain Style: Pop-up
Escutcheon Primary Material: Brass
Fittings Hole Diameter: 1 1/4"

Fittings Hole Diameter: 1 1/4"
Flow Restriction Options: 1.75, 1.5, 1.0
Handle Spread Maximum: 12"
Handle Spread Minimum: 8"
Handle Turn Angle: Quarter Turn
Depth / Width: 8"

Drain Depth Minimum: 1 3/8" Height: 2 3/4"

Inlet Connection Size: 1/2"

 $In let\ Connection\ Type:\ Male\ with\ Supply\ Nut$

Length: 14 1/2"

Number of Holes: Three Hole Primary Material: Brass

Restricted Maximum Flow Rate: 2.2 gpm

Spout Swivel: N

Suggested Application: Bath Valve Material: ceramic

Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi

Water Pressure Recommended: 45.0 psi

INSPIRATION

An easy and distinctive silhouette, Aero Retro is a softer version of Aero with a more informal feeling.

CODES & STANDARDS

 ${\sf Code \#RTLS01: ASME\ A112.18.1, CSA\ B125, NSF, CEC, IAPMO, State\ of\ MA}$

PRODUCT FEATURES

Brass material is used for all trim and valve component parts.

 $The \ manufacturing \ process \ encompasses \ casting, turning, hand-fitting \ and \ hand \ polishing.$

The unique handle is characterized by a concave bell escutcheon and a propeller-like spoke handle.

Standard flow rate is 2.2gpm (8.3 L/min) and State of California requires 1.2gpm(4.5 L/min). Also available in other flow options. Contact a sales associate for details.









PRODUCT (NOTES)

Sold with European style drain; USA style drain sold separately for use with non-Waterworks sinks.

AERO RETRO RTLS02

Aero Retro Low Profile Three Hole Deck Mounted Lavatory Faucet with Metal Lever Handles

