

## HIGHGATE

## HGXT40

Highgate Deck Mounted Exposed Tub Filler With Handshower and Metal Cross Handles



SHOWN IN HIGHGATE DECK MOUNTED EXPOSED TUB FILLER WITH HANDSHOWER AND METAL CROSS HANDLES | HGXT40

### TECHNICAL DETAILS

ADA Compliance: Yes  
 Adjustable Versus Fixed Spray: Fixed Spray  
 Deck Thickness Maximum: 1 7/8"  
 Deck Thickness Minimum: 0"  
 Depth/Width: 11 1/2"  
 Diameter Of Head: 2 3/4"  
 Diameter Of Legs Tubes: 1 1/8"  
 Escutcheon Primary Material: Brass  
 Fittings Hole Diameter: 1 1/4"  
 Flow Restriction Options: 2.0, 1.75, 1.5, 0.92  
 Handle Spread Maximum: 7 5/8"  
 Handle Spread Minimum: 7 5/8"  
 Handle Turn Angle: Quarter Turn  
 Handshower Spray Hose Length: 59"  
 Height: 15"  
 Index Color Finish And Material: White Porcelain  
 Index Marking: H/C  
 Inlet Connection Size: 3/4"  
 Inlet Connection Type: Male NPT Adapter  
 Inlet Supply Spread Maximum: 7 5/8"  
 Inlet Supply Spread Minimum: 7 5/8"  
 Installation Type: Deck Mounted  
 Integrated Diverter: N  
 Integrated Spray: N  
 Length: 9 15/16"  
 Number Of Handles: Three  
 Number Of Holes: Two Hole  
 Pivot: N  
 Primary Material: Brass  
 Spout Swivel: N  
 Spray Included In Unit: N  
 Suggested Application: Bath  
 Valve Material: Ceramic  
 Water Pressure Maximum: 85.0 psi  
 Water Pressure Minimum: 20.0 psi  
 Water Pressure Recommended: 45.0 psi

### INSPIRATION

Our take on old English style: simple, functional shapes, detailed with white porcelain indices and hexagonal accents for a timeless feel.

### CODES & STANDARDS

Code # HGXT40: Complies with ASME A112.18.1/CSA B125.1, CEC, ADA and 0.25% Weighted Average Lead Content. Certified with IAPMO, cUPC, CEC, DOE, State of MA and WRAS.

### PRODUCT FEATURES

The handshower is easy to grip offering a round spray pattern

All finishes available for immediate shipment (subject to availability)

Includes deck unions

Porcelain lever handles feature hot and cold markings on white porcelain indices

Stocked in 2.5gpm (7.6 L/min) and 1.75gpm (6.6 L/min) for Handshower. State of California requires 1.75gpm (6.6 L/min) to comply with their water conservation requirements. Other flow options are available to order, contact your sales associate or call 1 (800) 899-6757 for details

### CERTIFICATIONS



### PRODUCT (NOTES)

Includes deck unions. You are able to specify the Universal Floor Unions (UNUN32) to be used with Waterworks Studio Highgate Wall Mounted Exposed Tub Filler (HGXT20).

## HIGHGATE

HGXT40

Highgate Deck Mounted Exposed Tub Filler With Handshower and Metal Cross Handles

