

.25

PT71SH

.25 Wall Mounted 4 1/4" Shower Head, Arm and Flange



SHOWN IN NICKEL

TECHNICAL DETAILS

Adjustable versus Fixed Spray: Fixed Spray
 Diameter of Head: 108 mm
 Escutcheon Primary Material: Brass
 Fittings Hole Diameter: 32 mm
 Flow Restriction Options: 2.0
 Depth / Width: 308 mm
 Height: 162 mm
 Inlet Connection Size: 1/2"
 Inlet Connection Type: Male G/BSPP
 Installation Type: Wall Mounted
 Integrated Diverter: N
 Length: 105 mm
 Pivot: Y
 Primary Material: Brass
 Restricted Maximum Flow Rate: 9.5 liters/min
 Suggested Application: Bath
 Water Pressure Maximum: 6.0 bar
 Water Pressure Minimum: 1.5 bar
 Water Pressure Recommended: 3.0 bar

INSPIRATION

.25 is the ultimate in utilitarian elegance: A simple and understated design that is equally functional and beautiful.

CODES & STANDARDS

Code # : ASME A112.18.1 / CSA B125.1, IAPMO, State of MA

PRODUCT FEATURES

Clean lines and modern elegance define the .25 family
 Customize your shower experience with a shower head, arm, and flange
 Standard flow rate is 2.5gpm (9.5 L/min). Also available in high efficient flow options. Contact your sales associate or call 1 (800) 899-6757 for details.

.25

PT71SH

.25 Wall Mounted 4 1/4" Shower Head, Arm and Flange

