WATERWORKS

JULIA JUKM12

Julia Two Hole Bridge High Profile Kitchen Faucet, Metal Cross Handles



TECHNICAL DETAILS

ADA Compliance: Yes Adjustable versus Fixed Spray: Fixed Spray Deck Thickness Maximum: 2 1/4" Deck Thickness Minimum: 0" Escutcheon Primary Material: Brass Fittings Hole Diameter: 1" Flow Restriction Options: 1.5, 1.0 Handle Spread Maximum: 7 7/8" Handle Spread Minimum: 7 7/8" Handle Turn Angle: Quarter Turn Index Color / Finish and Material: White Porcelain Depth / Width: 11 1/4" Height: 8 7/8" Index Marking: Hot/Cold Inlet Connection Size: 1/2" Inlet Connection Type: Straight Male Threads Inlet Supply Spread Maximum: 7 7/8" Inlet Supply Spread Minimum: 7 7/8" Length: 10 3/8" Number of Handles: Two Number of Holes: Two Hole Primary Material: Brass Restricted Maximum Flow Rate: 2.2 gpm Spout Swivel: Y Spray Included in Unit: N Suggested Application: Bar, Kitchen, Laundry Valve Material: Ceramic Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi

SHOWN IN JULIA TWO HOLE BRIDGE HIGH PROFILE KITCHEN FAUCET, METAL CROSS HANDLES| JUKM12

INSPIRATION

An interpretation of 1920s French country, Julia speaks to decoration and intricate design displayed through beautifully composed turnings. These details embody the robust, signature high profile spout enabling Julia to transition fluidly from informal to formal environments.

CODES & STANDARDS

Water Pressure Recommended: 45.0 psi

Code # JUKM12: ASME A112.18.1 / CSA B125.1, NSF, CEC, State of MA

PRODUCT FEATURES

Exposed mixer features signature detail of the graceful, high profile swivel spout, and metal indices engraved in a simplistic "H" or "C". The addition of a kitchen spray completes the look and funtionality of any kitchen.

Standard flow rate is 2.2gpm (8.3 L/min) and State of California requires a maximum of 1.8gpm(6.8 L/min). Also available in other flow options. Contact a sales associate for details.









JULIA JUKM12

Julia Two Hole Bridge High Profile Kitchen Faucet, Metal Cross Handles

