

REGULATOR

RG50KM

Regulator Gooseneck Double Spout Marquee Kitchen Faucet, Black Wheel Handles and Spray



SHOWN IN REGULATOR GOOSENECK DOUBLE SPOUT MARQUEE KITCHEN FAUCET, BLACK WHEEL HANDLES AND SPRAY|

TECHNICAL DETAILS

Deck Thickness Maximum: 51 mm
Deck Thickness Minimum: 6 mm
Handle Spread Maximum: 305 mm
Handle Spread Minimum: 152 mm
Handle Turn Angle: Quarter Turn Each Way
Handshower / Spray Hose Length: 2.0 m
Depth / Width: 314 mm
Height: 403 mm
Inlet Connection Size: 3/8"
Inlet Connection Type: Female BSPP
Integrated Diverter: Y
Integrated Spray: N
Length: 772 mm
Primary Material: Brass
Restricted Maximum Flow Rate: 8.3 liters/min
Spout Swivel: Y
Spray Included in Unit: Y
Suggested Application: Bar, Kitchen, Laundry
Valve Material: Ceramic
Water Pressure Maximum: 5.5 bar
Water Pressure Minimum: 1.5 bar
Water Pressure Recommended: 3.0 bar

INSPIRATION

A play on industrial controls from the early 1900s, when pride was lavished on parts. Translated to handcrafted, fittings project rugged beauty through powerful, detailed shapes.

PRODUCT FEATURES

Casted brass temperature mixing valve. The user rotates the center control handle for preferred temperature.
Solid brass wheel handles finished in matte black to control on/off/volume. Paint resistant to hard water
Built-in automatic diverters for spray operation.
Larger holes are required in the deck. 2-1/4" for mixing valve. 1-3/4" for faucet spouts.

PRODUCT (NOTES)

Drilling size requirements are 2 1/4" for mixing/spray body and 1 3/4" for faucet body.

REGULATOR

RG50KM

Regulator Gooseneck Double Spout Marquee Kitchen Faucet, Black Wheel Handles and Spray

