DSLS01 DASH

Dash Low Profile Three Hole Deck Mounted Lavatory Faucet with **Metal Cross Handles**



SHOWN IN DASH LOW PROFILE THREE HOLE DECK MOUNTED LAVATORY FAUCET WITH METAL CROSS HANDLES DSLS01

INSPIRATION

A blend of art and function, Dash pays homage to design elements of the 1930s with pared-down shapes, softened curves and minimal details.

PRODUCT FEATURES

Metal Cross Handle

Includes European push touch style drain.

Stocked in Nickel, Chrome, Unlacquered Brass, and Matte Nickel finishes

Standard flow rate is 2.2gpm (8.3 L/min) and State of California requires 1.2gpm(4.5 L/min). Also available in other flow options. Contact a sales associate for details.

TECHNICAL DETAILS

Deck Thickness Maximum: 40 mm

Deck Thickness Minimum: 6 mm

Drain Assembly Materials: Brass, Rubber, Plastic

Drain Depth Maximum: 67 mm Drain Hole Diameter: 44 mm

Drain Style: Push-Touch

Escutcheon Primary Material: Brass

Fittings Hole Diameter: 35 mm

Flow Restriction Options: 1.75, 1.5, 1.2, 1.0

Handle Spread Maximum: 305 mm

Handle Spread Minimum: 203 mm

Handle Turn Angle: Quarter Turn

Depth / Width: 195 mm

Drain Depth Minimum: 10 mm

Height: 94 mm

Inlet Connection Size: 1/2"

Inlet Connection Type: Male with Supply Nut

Inlet Supply Spread Maximum: 305 mm

Inlet Supply Spread Minimum: 203 mm Installation Type: Deck Mounted

Length: 303 mm

Number of Handles: Two

Number of Holes: Three Hole

Primary Material: Brass

Restricted Maximum Flow Rate: 8.3 liters/min

Spout Swivel: N

Suggested Application: Bath

Valve Material: Ceramic

Water Pressure Maximum: 6.0 bar Water Pressure Minimum: 1.5 bar

Water Pressure Recommended: 3.0 bar

DASH DSLS01

Dash Low Profile Three Hole Deck Mounted Lavatory Faucet with Metal Cross Handles

