WATERWORKS

HNLS02 **HENRY**

Henry Low Profile Three Hole Deck Mounted Lavatory Faucet with Teak Cylinders and Metal Cross Handles



TECHNICAL DETAILS

Adjustable versus Fixed Spray: Fixed Spray

Deck Thickness Maximum: 41 mm Deck Thickness Minimum: 5 mm Drain Depth Maximum: 67 mm Drain Hole Diameter: 44 mm **Escutcheon Primary Material: Brass** Fittings Hole Diameter: 32 mm Handle Spread Maximum: 305 mm Handle Spread Minimum: 203 mm Handle Turn Angle: Ouarter Turn Depth / Width: 194 mm Drain Depth Minimum: 10 mm Height: 92 mm Inlet Connection Size: 1/2" Inlet Connection Type: Male with Supply Nut Inlet Supply Spread Maximum: 305 mm Inlet Supply Spread Minimum: 203 mm Installation Type: Deck Mounted Integrated Diverter: N Integrated Spray: N Number of Handles: Two Number of Holes: Three Hole Primary Material: Brass Restricted Maximum Flow Rate: 4.5 liters/min Spout Swivel: N Spray Included in Unit: N Suggested Application: Bath Valve Material: Ceramic Water Pressure Maximum: 6.0 bar Water Pressure Minimum: 1.5 bar Water Pressure Recommended: 3.0 bar

SHOWN IN HENRY LOW PROFILE THREE HOLE DECK MOUNTED LAVATORY FAUCET WITH TEAK CYLINDERS AND METAL

INSPIRATION

Influenced by the connection of industry and art Henry easily transitions between modern, traditional, utilitarian and classic settings.

CODES & STANDARDS

Code # HNLS02X: Complies with ASME A112.18.1/CSA B125.1, ASME A112.18.2 / CSA B125.2, NSF, CEC 61, ADA and 0.25% Weighted Average Lead Content. Certified with IAPMO, cUPC, NSF, CEC and State of MA.

PRODUCT FEATURES

Metal cross handles with teak cylinders Includes European size push touch drain Teak is an organic, natural hardwood originating from Southeast Asia Stocked in Chrome, Nickel, Matte Nickel, and Unlacquered Brass Available in 1.2gpm (4.5L/min) flow rate

CERTIFICATIONS



HENRY HNLS02

Henry Low Profile Three Hole Deck Mounted Lavatory Faucet with Teak Cylinders and Metal Cross Handles

