DSLS70 DASH

Dash Three Hole Wall Mounted Lavatory Faucet with Metal Lever Handles



SHOWN IN DASH THREE HOLE WALL MOUNTED LAVATORY FAUCET WITH METAL LEVER HANDLES| DSLS70

INSPIRATION

A blend of art and function, Dash pays homage to design elements of the 1930s with pared-down shapes, softened curves and minimal details.

PRODUCT FEATURES

Metal Lever Handle

Includes European push touch style drain.

Stocked in Nickel, Chrome, Unlacquered Brass, and Matte Nickel finishes

Standard flow rate is 2.2gpm (8.3 L/min) and State of California requires 1.2gpm(4.5 L/min). Also available in other flow options. Contact a sales associate for details.

TECHNICAL DETAILS

Control Valve Rough-in Depth Maximum: 140 mm Control Valve Rough-in Depth Minimum: 76 mm Drain Assembly Materials: Brass, Rubber, Plastic Drain Depth Maximum: 67 mm Drain Hole Diameter: 44 mm Drain Style: Push-Touch Escutcheon Primary Material: Brass

Fittings Hole Diameter: 35 mm Flow Restriction Options: 1.75, 1.5, 1.2, 1.0 Handle Spread Maximum: 203 mm Handle Spread Minimum: 203 mm

Handle Turn Angle: Quarter Turn Depth / Width: 198 mm Drain Depth Minimum: 10 mm

Height: 73 mm

Inlet Connection Size: 1/2" Inlet Connection Type: Male NPT Inlet Supply Spread Maximum: 203 mm Inlet Supply Spread Minimum: 203 mm Installation Type: Wall Mounted Length: 383 mm Number of Handles: Two Number of Holes: Three Hole

Primary Material: Brass Restricted Maximum Flow Rate: 8.3 liters/min Spout Swivel: N

Suggested Application: Bath Water Pressure Maximum: 6.0 bar Water Pressure Minimum: 1.5 bar Water Pressure Recommended: 3.0 bar

PRODUCT (NOTES)

Product Requires Universal Lavatory Wall Mounted Rough Valve [GULV25]. Valve Sold Separately.

DASH DSLS70

Dash Three Hole Wall Mounted Lavatory Faucet with Metal Lever Handles

