WATERWORKS

EALS34 **EASTON**

Easton Classic Gooseneck Three Hole Deck Mounted Lavatory Faucet with Black Porcelain Lever Handles



TECHNICAL DETAILS

Adjustable versus Fixed Spray: Fixed Spray Deck Thickness Maximum: 1 1/4" Deck Thickness Minimum: 0" **Drain Assembly Materials: Brass** Drain Depth Maximum: 2 3/4" Drain Hole Diameter: 1 3/4"

Fittings Hole Diameter: 1 3/8" Flow Restriction Options: 1.0, 1.2, 1.5, 1.75, 2.2

Handle Spread Maximum: 12" Handle Spread Minimum: 8" Handle Turn Angle: Quarter Turn

Index Color / Finish and Material: White Porcelain

Depth / Width: 8 1/2" Drain Depth Minimum: 1" Height: 6 1/2" Inlet Connection Size: 1/2"

Inlet Connection Type: Male with supply nut

Inlet Supply Spread Maximum: 12" Inlet Supply Spread Minimum: 8" Installation Type: Deck Mounted

Length: 15"

Number of Holes: Three Hole Primary Material: Brass Spout Swivel: N Suggested Application: Bath Valve Material: Ceramic

Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN EASTON CLASSIC GOOSENECK THREE HOLE DECK MOUNTED LAVATORY FAUCET WITH BLACK PORCELAIN

INSPIRATION

Drawing on Edwardian style, Easton is the most extensive Waterworks family; a range of moods and a selection of products from fittings to furniture.

CODES & STANDARDS

Code # EALS34: CEC

PRODUCT FEATURES

Standard flow rate is 2.2gpm (8.3 L/min) and State of California requires 1.2gpm(4.5 L/min). Also available in other flow options. Contact a sales associate for details.

CERTIFICATIONS



PRODUCT (NOTES)

Sold with European style drain; USA style drain sold separately for use with non-Waterworks sinks.

EASTON EALS34

Easton Classic Gooseneck Three Hole Deck Mounted Lavatory Faucet with Black Porcelain Lever Handles

