## WATERWORKS

EASTON EALS55

Easton Vintage Gooseneck Three Hole Deck Mounted Lavatory Faucet with Oak Lever Handles



#### **TECHNICAL DETAILS**

Adjustable versus Fixed Spray: Fixed Spray
Deck Thickness Maximum: 1 1/4"
Deck Thickness Minimum: 0"
Drain Assembly Materials: Brass
Drain Depth Maximum: 2 3/4"
Drain Hole Diameter: 1 3/4"
Fittings Hole Diameter: 1 3/8"
Handle Spread Maximum: 12"
Handle Spread Minimum: 8"
Handle Turn Angle: Quarter Turn
Index Color / Finish and Material: White Porcelain
Depth / Width: 8 1/2"
Drain Depth Minimum: 1"
Height: 6 1/2"
Inlet Connection Size: 1/2"

Inlet Connection Type: Male with supply nut Inlet Supply Spread Maximum: 12" Inlet Supply Spread Minimum: 8" Installation Type: Deck Mounted

Installation Type: Deck Mounte Length: 15" Number of Holes: Three Hole

Primary Material: Brass Restricted Maximum Flow Rate: 1.2 gpm

Spout Swivel: N Suggested Application: Bath Valve Material: Ceramic Water Pressure Maximum: 85.0 psi

Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

L SHOWN IN EASTON VINTAGE GOOSENECK THREE HOLE DECK MOUNTED LAVATORY FAUCET WITH OAK LEVER HANDLES|

#### **INSPIRATION**

Drawing on Edwardian style, Easton is the most extensive Waterworks family; a range of moods and a selection of products from fittings to furniture.

### **CODES & STANDARDS**

Code # EALS55: CEC

#### **PRODUCT FEATURES**

Available in 1.2gpm (4.5L/min) flow rate

#### **CERTIFICATIONS**



#### PRODUCT (NOTES)

Sold with European style drain; USA style drain sold separately for use with non-Waterworks sinks.

# EASTON EALS55

Easton Vintage Gooseneck Three Hole Deck Mounted Lavatory Faucet with Oak Lever Handles

