REGULATOR RGXT20

Regulator Exposed Wall Mounted Tub Filler with Handshower and Black Wheel Handles



## **TECHNICAL DETAILS**

Adjustable Versus Fixed Spray: Fixed Depth/Width: 11 13/16"
Fittings Hole Diameter: 1 3/8"

Flow Restriction Options: 2.5, 2.0, 1.75, 1.5, 0.92

Handle Turn Angle: Quarter Turn Handshower Spray Hose Length: 59"

Height: 12"

Inlet Connection Size: 3/4"
Inlet Connection Type: Compression
Inlet Supply Spread Maximum: 8"
Inlet Supply Spread Minimum: 8"
Integrated Diverter: Y
Integrated Spray: Y
Length: 12 3/8"
Primary Material: Brass

Suggested Application: Bath Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN REGULATOR EXPOSED WALL MOUNTED TUB FILLER WITH HANDSHOWER AND BLACK WHEEL HANDLES | RGXT20

INSPIRATION CODES & STANDARDS

A play on industrial controls from the early 1900s, when pride was lavished on parts. Translated to handcrafted, fittings project rugged beauty through powerful, detailed shapes.

## PRODUCT FEATURES

Matte Black Wheel

Includes Required Unions for Mounting

Exposed Tub Fillers feature a unique shut-off and diverter valve inside the decorative valve body. Handshower features anti-drip technology.

Stocked in Nickel, Chrome and Unlacquered Brass

Stocked in 2.5gpm (9.5 L/min) and 1.75gpm (6.6 L/min) for handshower. State of California requires 1.75gpm (6.6 L/min) to comply with their water conservation requirements. Other flow options are available to order, contact your sales associate or call 1 (800) 899-6757 for details.

## **CERTIFICATIONS**

## PRODUCT (NOTES)

REGULATOR RGXT20

Regulator Exposed Wall Mounted Tub Filler with Handshower and Black Wheel Handles

