

R.W. ATLAS

RW01XS

R.W. Atlas Exposed Thermostatic Valve with Metal Wheel Handles



SHOWN IN BURNISHED NICKEL WITH WHEEL HANDLE

TECHNICAL DETAILS

ADA Compliance: Yes
Adjustable versus Fixed Spray: Fixed Spray
Diameter of Head: 217 mm
Escutcheon Primary Material: Brass
Fittings Hole Diameter: 25 mm
Flow Restriction Options: 2.0, 1.75, 1.5, 0.92
Handshower / Spray Hose Length: 1.5 m
Depth / Width: 181 mm
Height: 249 mm
Inlet Connection Size: 3/4"
Inlet Connection Type: Male G/BSPP
Inlet Supply Spread Maximum: 298 mm
Inlet Supply Spread Minimum: 292 mm
Installation Type: Wall Mounted
Integrated Diverter: N
Length: 351 mm
Number of Handles: One
Pivot: N
Primary Material: Brass
Restricted Maximum Flow Rate: 9.5 liters/min
Spray Included in Unit: N
Suggested Application: Bath
Valve Material: Bi-metal Strip
Water Pressure Maximum: 5.5 bar
Water Pressure Minimum: 1.5 bar
Water Pressure Recommended: 3.0 bar

INSPIRATION

A groundbreaking, industrial-inspired collection entices with powerful shapes, genuine materials and unique aesthetic details. The original vision and impeccable execution of R.W. Atlas pairs American ingenuity with European craftsmanship.

CODES & STANDARDS

Code # : Certified with IAPMO & State of MA. Complies with ASME A112.18.1/CSA B125.1, ANSI 117.1 ADA & ASTM E 1621-05.

PRODUCT FEATURES

Features knurled detail on the handle.

Maintains concealed piping for shower head and handshower options.

Features temperature engraved markings H, C and 100 degrees.

Offers a temperature limit stop with override button.

Standard flow rate is 2.5gpm for handshower only. Also available in high efficiency flow options.

Contact your sales associate or call 1 (800) 899-6757 for details.

R.W. ATLAS

RW01XS

R.W. Atlas Exposed Thermostatic Valve with Metal Wheel Handles

