

WATERWORKS

PRODUCT SUPPORT
800.927.2120
WATERWORKS.COM

EASTON CLASSIC

Classic Low Profile Concealed Tub Filler
With Handshower and White Porcelain
Lever Handles in Chrome

STYLE No. 961579

REFERENCE No. EATU03C-K

ITEM No. 09-12602-42216

SPECIFICATIONS
PAGE 1 OF 3

DESIGN

A stylish update of the quintessential Edwardian fitting, Easton provides vintage luxury for the 21st century. Proportion and detailing resonate with the indulgence of a bygone era, while the sense of fit and function are purely contemporary.

FEATURES

Brass metal is used for all trim and valve components.

Optional handle materials include porcelain and semi-precious stones.

The manufacturing process encompasses casting, turning, forging, hand-fitting and hand polishing.

The pillowed propeller on the cross handle makes the product fit comfortably in the hand.

An extensive range of fittings, fixture and accessory options for the lavatory, bath and kitchen.



SHOWN IN Nickel

PRODUCT SUPPORT
800.927.2120
WATERWORKS.COM

Classic Low Profile Concealed Tub Filler
With Handshower and White Porcelain
Lever Handles in Chrome

STYLE No. 961579
REFERENCE No. EATU03C-K
ITEM No. 09-12602-42216

PAGE 2 OF 3

All dimensions are based on original specifications and are subject to change and variation. Please consult your Design Associate for current specifications.



SCALE: 1 1/2"=1'-0"



SCALE: 1 1/2"=1'-0"



SCALE: 1 1/2"=1'-0"

WATERWORKS

PRODUCT SUPPORT
800.927.2120
WATERWORKS.COM

EASTON CLASSIC

Classic Low Profile Concealed Tub Filler
With Handshower and White Porcelain
Lever Handles in Chrome

STYLE No. 961579

REFERENCE No. EATU03C-K

ITEM No. 09-12602-42216

SPECIFICATIONS

PAGE 3 OF 3

SPECIFICATIONS

Primary Material: Brass
Handle Spread Maximum:
Handle Spread Minimum: 10"
Inlet Connection Size: $\frac{3}{4}$ "
Inlet Connection Type: Male NPT
Inlet Supply Spread Maximum:
Inlet Supply Spread Minimum: 10"
Maximum Deck Thickness: 1 $\frac{1}{2}$ "
Minimum Deck Thickness: 0"
Maximum Water Pressure: 75 psi
Minimum Water Pressure: 20 psi
Fittings Hole Diameter: 1 $\frac{3}{8}$ "
Recommended Water Pressure: 45 psi

CARE INSTRUCTIONS

To clean the finish, wipe gently with a soft damp cloth and then with a soft dry towel. A mild soap solution can be used for daily cleaning.

CODES AND STANDARDS

ASME A112.18.1, CSA B125, ASSE 1014, IAPMO, State of MA

FLOW RATE CURVE

REQUIRED PLUMBING DETAILS

Below is a list of choices that must be made to complete your lavatory faucet.