WATERWORKS

EASTON EAKM17

Easton Vintage Spray, Metal Lever Handle



TECHNICAL DETAILS

ADA Compliance: Yes Adjustable versus Fixed Spray: Fixed Spray Deck Thickness Maximum: 32 mm Deck Thickness Minimum: 0 mm Escutcheon Primary Material: Brass Fittings Hole Diameter: 35 mm Flow Restriction Options: 2.0, 1.75, 1.5 Handle Turn Angle: Quarter Turn Handshower / Spray Hose Length: 1.2 m

Index Color / Finish and Material: White Porcelain Depth / Width: 64 mm Height: 152 mm Index Marking: Waterworks

Inlet Connection Size: 1/2" Inlet Connection Type: Male with Supply Nut Integrated Diverter: N

Length: 178 mm
Number of Handles: One
Number of Holes: Two Hole
Primary Material: Brass

Restricted Maximum Flow Rate: 8.3 liters/min

Spray Included in Unit: Y

Suggested Application: Bar, Kitchen, Laundry Valve Material: Ceramic

Water Pressure Maximum: 6.0 bar Water Pressure Minimum: 1.5 bar Water Pressure Recommended: 3.0 bar

SHOWN IN EASTON VINTAGE SPRAY, METAL LEVER HANDLE EAKM17

INSPIRATION

Drawing on Edwardian style, Easton is the most extensive Waterworks family; a range of moods and a selection of products from fittings to furniture.

CODES & STANDARDS

Code # EAKM17: ASME A112.18.1, CSA B125, NSF, IAPMO, CEC, State of MA $\,$

PRODUCT FEATURES

Brass metal is used for all trim and valve components

The manufacturing process encompasses casting, turning, forging, hand-fitting and hand polishing. Easton is our most comprehensive fittings family.

Easton has a clean-lined utilitarian profile, with a slightly elongated spout.

Standard flow rate is 2.2gpm (8.3 L/min) and State of California requires a maximum of 1.8gpm(6.8 L/min). Also available in other flow options. Contact a sales associate for details.

CERTIFICATIONS



EASTON EAKM17

Easton Vintage Spray, Metal Lever Handle

