FORMWORK FMLS60

Formwork Low Profile Three Hole Wall Mounted Lavatory Faucet with Metal Knob Handles



TECHNICAL DETAILS

ADA Compliance: Yes

Adjustable Versus Fixed Spray: Fixed Spray

Depth/Width: 9 1/16"

Drain Depth Maximum: 1 3/4" Drain Depth Minimum: 1 1/2" Drain Hole Diameter: 1 3/4" Drain Style: Push Touch

Escutcheon Primary Material: Brass

Fittings Hole Diameter: 1 3/8"

Flow Restriction Options: 1.0 , 1.2 , 1.5 , 1.75, 2.2

Handle Spread Maximum: 8" Handle Spread Minimum: 8" Handle Turn Angle: Quarter Turn

Height: 6"

Inlet Connection Size: 1/2"
Inlet Connection Type: Female NPT
Inlet Supply Spread Maximum: 8"
Inlet Supply Spread Minimum: 8"
Installation Type: Wall Mounted

Integrated Diverter: N Integrated Spray: N Length: 10 3/8"

Number Of Handles: Two Number Of Holes: Three Hole Primary Material: Brass Spout Swivel: N Spray Included In Unit: N Suggested Application: Bath

Valve Material: Ceramic Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi

Water Pressure Recommended: 45.0 psi

SHOWN IN FORMWORK LOW PROFILE THREE HOLE WALL MOUNTED LAVATORY FAUCET WITH METAL KNOB HANDLES | FMLS60

INSPIRATION

Sculptural forms that defy the ordinary. Unexpected geometry and the transition of the planes create a subtle but warm expression.

CODES & STANDARDS

Code # FMLS60X: Certified with cUPC, NSF, CEC, IAPMO,

PRODUCT FEATURES

Knob Handles

Modern Push-Touch Euro style drain included.

Standard flow rate is 2.2gpm (8.3 L/min) and State of California requires 1.2gpm(4.5 L/min). Also available in other flow options. Contact a sales associate for details.

CERTIFICATIONS





PRODUCT (NOTES)

FORMWORK FMLS60

Formwork Low Profile Three Hole Wall Mounted Lavatory Faucet with Metal Knob Handles

