

REGULATOR

RGXT41

Regulator Exposed Deck Mounted Tub Filler with Handshower and Metal Wheel Handles



SHOWN IN REGULATOR EXPOSED DECK MOUNTED TUB FILLER WITH HANDSHOWER AND METAL WHEEL HANDLES | RGXT41

TECHNICAL DETAILS

Adjustable Versus Fixed Spray: Fixed
Deck Thickness Maximum: 2 1/2"
Deck Thickness Minimum: 1/4"
Depth/Width: 11 13/16"
Fittings Hole Diameter: 1 3/8"
Flow Restriction Options: 2.5, 2.0, 1.75, 1.5, 0.92
Handle Turn Angle: Quarter Turn
Handshower Spray Hose Length: 59"
Height: 19 7/8"
Inlet Connection Size: 3/4"
Inlet Connection Type: Male BSPP
Inlet Supply Spread Maximum: 8"
Inlet Supply Spread Minimum: 8"
Integrated Diverter: Y
Integrated Spray: Y
Length: 12 3/8"
Primary Material: Brass
Suggested Application: Bath
Water Pressure Maximum: 85.0 psi
Water Pressure Minimum: 20.0 psi
Water Pressure Recommended: 45.0 psi

INSPIRATION

A play on industrial controls from the early 1900s, when pride was lavished on parts. Translated to handcrafted, fittings project rugged beauty through powerful, detailed shapes.

CODES & STANDARDS

PRODUCT FEATURES

Metal Wheel Handle

Includes Required Unions for Mounting

Exposed Tub Fillers feature a unique shut-off and diverter valve inside the decorative valve body. Handshower features anti-drip technology.

Stocked in Nickel, Chrome and Unlacquered Brass

Stocked in 2.5gpm (9.5 L/min) and 1.75gpm (6.6 L/min) for handshower. State of California requires 1.75gpm (6.6 L/min) to comply with their water conservation requirements. Other flow options are available to order, contact your sales associate or call 1 (800) 899-6757 for details.

CERTIFICATIONS

PRODUCT (NOTES)

REGULATOR

RGXT41

Regulator Exposed Deck Mounted Tub Filler with
Handshower and Metal Wheel Handles

