WATERWORKS

FLYTE FLLSo1

Flyte Low Profile Three Hole Deck Mounted Lavatory Faucet with Metal Cross Handles



TECHNICAL DETAILS

ADA Compliance: Yes
Adjustable versus Fixed Spray: Fixed Spray
Deck Thickness Maximum: 2 1/2"
Deck Thickness Minimum: 3/8"
Drain Depth Maximum: 2"
Drain Hole Diameter: 1 1/2"
Escutcheon Primary Material: Brass
Fittings Hole Diameter: 1 3/8"
Flow Restriction Options: 1.0
Handle Spread Maximum: 12"
Handle Spread Minimum: 8"
Handle Turn Angle: Quarter Turn
Depth / Width: 7 5/8"

Drain Depth Minimum: 1 1/4" Height: 4 1/8"

Number of Holes: Three Hole

Height: 4 1/8"
Inlet Connection Size: 1/2"
Inlet Connection Type: Male with Supply Nut
Inlet Supply Spread Maximum: 12"
Inlet Supply Spread Minimum: 8"
Installation Type: Deck Mounted
Integrated Diverter: N
Integrated Spray: N
Length: 15 1/4"
Number of Handles: Two

Primary Material: Brass Restricted Maximum Flow Rate: 1.5 gpm Spout Reach: 6" Spout Swivel: N Spray Included in Unit: N Suggested Application: Bath Valve Material: Ceramic Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN CHROME

INSPIRATION

Clean lines and simple geometric shapes are enhanced by perfect proportions in this light and fluid collection. Flyte offers a uniquely striking way to accent a modern bath.

CODES & STANDARDS

Code # FLLSo1:

PRODUCT FEATURES

Push touch USA style drain included.

This item is stocked in a Chrome and Nickel finishes

Cross Handles

Standard flow rate 1.5gpm (5.7 L/min). Also available in high efficient flow options. Contact your sales associate or call 1 (800) 899-6757 for details.

CERTIFICATIONS





FLYTE FLLSo1

Flyte Low Profile Three Hole Deck Mounted Lavatory Faucet with Metal Cross Handles

