WATERWORKS

EASTON EAKM09

Easton Classic Spray, Black Porcelain Lever Handle



TECHNICAL DETAILS

ADA Compliance: Yes
Adjustable versus Fixed Spray: Fixed Spray
Deck Thickness Maximum: 32 mm
Deck Thickness Minimum: 0 mm
Fittings Hole Diameter: 35 mm
Flow Restriction Options: 2.0, 1.75, 1.5
Handle Turn Angle: Quarter Turn
Handshower / Spray Hose Length: 1.2 m
Index Color / Finish and Material: White Porcelain
Depth / Width: 64 mm

Inlet Connection Size: 1/2"
Inlet Connection Type: Male with Supply Nut

Length: 178 mm

Number of Holes: Two Hole
Primary Material: Brass

Height: 152 mm

Restricted Maximum Flow Rate: 8.3 liters/min

Spray Included in Unit: N

Suggested Application: Bar, Kitchen, Laundry Valve Material: Ceramic

Water Pressure Maximum: 6.0 bar Water Pressure Minimum: 1.5 bar Water Pressure Recommended: 3.0 bar

SHOWN IN EASTON CLASSIC SPRAY, BLACK PORCELAIN LEVER HANDLE EAKM09

INSPIRATION

Drawing on Edwardian style, Easton is the most extensive Waterworks family; a range of moods and a selection of products from fittings to furniture.

CODES & STANDARDS

Code # EAKM09: Complies with ASME A112.18.1/CSA B125.1, NSF 61, NSF 372, CEC, ADA and 0.25% Weighted Average Lead Content.
Certified with IAPMO, cUPC, NSF, CEC, DOE and State of MA.

PRODUCT FEATURES

Brass metal is used for all trim and valve components

The manufacturing process encompasses casting, turning, forging, hand-fitting and hand polishing. Easton is our most comprehensive fittings family.

Easton has a clean-lined utilitarian profile, with a slightly elongated spout.

Standard flow rate is 2.2gpm (8.3 L/min) and State of California requires a maximum of 1.8gpm(6.8 L/min). Also available in other flow options. Contact a sales associate for details.

CERTIFICATIONS







EASTON EAKM09

Easton Classic Spray, Black Porcelain Lever Handle

