

FLYTE

Flyte Volume Control Valve Trim with Metal Lever Handle

FLVC50



SHOWN IN FLYTE VOLUME CONTROL VALVE TRIM WITH METAL LEVER HANDLE| FLVC50

TECHNICAL DETAILS

ADA Compliance: Yes
Control Valve Rough-in Depth Maximum: 4 1/4"
Control Valve Rough-in Depth Minimum: 3 1/4"
Escutcheon Primary Material: Brass
Fittings Hole Diameter: 1 3/8"
Depth / Width: 2 5/16"
Height: 4 5/16"
Integrated Diverter: N
Integrated Spray: N
Length: 2 3/8"
Number of Handles: One
Pivot: N
Primary Material: Brass
Spout Swivel: N
Spray Included in Unit: N
Suggested Application: Bath

INSPIRATION

Pure Modernism. Like minimalist works of art, the elegant proportions of these light, fluid elements bring sculptural reference to a room.

CODES & STANDARDS

Code # FLSV50: Complies with ASME A112.18.1/CSA B125.1, ASTM E 1621-05, ANSI A117.1 ADA. Certified with IAPMO, cUPC & State of MA

PRODUCT FEATURES

Lever Handles

This item is stocked in a Chrome and Nickel finishes.

Required 1/2" valve rough Hot -GUV18(USA) or GU18VC(UK). Cold -GUV19(USA) or GU19VC(UK), sold separately.

This item is stocked in a Chrome, Nickel, and Graphite finishes

CERTIFICATIONS




PRODUCT (NOTES)

Required 1/2" valve rough Hot -GUV18 or Cold -GUV19, sold separately.


FLYTE

FLVC50


Flyte Volume Control Valve Trim with Metal Lever Handle



TOP VIEW SCALE: 3"=1'-0"



FRONT VIEW SCALE: 3"=1'-0"



SIDE VIEW SCALE: 3"=1'-0"