R.W. ATLAS RW10KM

R.W. Atlas Two Hole Bridge High Profile Kitchen Faucet, Metal Side Mount Levers and Spray



L SHOWN IN R.W. ATLAS TWO HOLE BRIDGE HIGH PROFILE KITCHEN FAUCET, METAL SIDE MOUNT LEVERS AND SPRAY|

INSPIRATION

Powerful shapes, genuine materials and unique aesthetic details. The original, impeccable vision of R.W. Atlas pairs American ingenuity with European craftsmanship.

PRODUCT FEATURES

Features horizontally mounted lever handles on the exposed valve body, available only with smooth barrels marked with an engraved H and C.

Integrated side spray allows for mixed water and features knurled detail on handle.

Meets or exceeds the Weighted Average Lead Requirements of 0.25%.

Standard flow rate is 2.2gpm (8.3 L/min). Also available in high efficiency flow options. Contact your sales associate or call 1 (800) 899-6757 for details.

TECHNICAL DETAILS

ADA Compliance: Yes
Adjustable versus Fixed Spray: Fixed Spray
Deck Thickness Maximum: 33 mm
Deck Thickness Minimum: 0 mm
Escutcheon Primary Material: Brass
Fittings Hole Diameter: 35 mm
Flow Restriction Options: 2.0, 1.75, 1.5
Handle Spread Maximum: 203 mm
Handle Spread Minimum: 203 mm
Handle Turn Angle: Quarter Turn
Handshower / Spray Hose Length: 1.2 m

Depth / Width: 300 mm Height: 259 mm

Inlet Connection Size: 3/8"
Inlet Connection Type: Female G/BSPP

Integrated Diverter: N Length: 537 mm Number of Handles: Two Number of Holes: Two Hole Primary Material: Brass

Restricted Maximum Flow Rate: 8.3 liters/min Spout Swivel: N

Spray Included in Unit: Y
Suggested Application: Bar, Kitchen, Laundry
Valve Material: Ceramic

Water Pressure Maximum: 5.5 bar

Water Pressure Minimum: 1.5 bar Water Pressure Recommended: 3.0 bar

R.W. ATLAS RW10KM

R.W. Atlas Two Hole Bridge High Profile Kitchen Faucet, Metal Side Mount Levers and Spray

