

## ODEON

ODKM13

Odeon One Hole Low Profile Kitchen Faucet with Pull-Out Spray and Metal Lever Handle



SHOWN IN ODEON ONE HOLE LOW PROFILE KITCHEN FAUCET WITH PULL-OUT SPRAY AND METAL LEVER HANDLE

### TECHNICAL DETAILS

ADA Compliance: No  
 Adjustable versus Fixed Spray: Fixed Spray  
 Deck Thickness Maximum: 1 5/8"  
 Deck Thickness Minimum: 0"  
 Escutcheon Primary Material: Brass  
 Fittings Hole Diameter: 1 3/8"  
 Flow Restriction Options: 2.0, 1.75, 1.5  
 Handle Turn Angle: Quarter Turn Each Way  
 Depth / Width: 11 7/8"  
 Height: 10 1/4"  
 Inlet Connection Size: 3/8"  
 Inlet Connection Type: Compression Connector Hoses  
 Inlet Supply Spread Maximum: 1"  
 Inlet Supply Spread Minimum: 1"  
 Integrated Diverter: N  
 Interior / Exterior Application: Interior Only  
 Length: 2 1/2"  
 Number of Handles: One  
 Number of Holes: One Hole  
 Primary Material: Brass  
 Restricted Maximum Flow Rate: 2.2 gpm  
 Spout Swivel: Y  
 Spray Included in Unit: N  
 Suggested Application: Bar, Kitchen, Laundry  
 Valve Material: Ceramic  
 Water Pressure Maximum: 85.0 psi  
 Water Pressure Minimum: 20.0 psi  
 Water Pressure Recommended: 45.0 psi

### INSPIRATION

Functionality, versatility, and convenience are key components of the Odeon Kitchen Mixer. Bridging a transitional environment this kitchen mixer is equally at home in a traditional or modern space.

### CODES & STANDARDS

Code # WWKM13: IAPMO, CEC

### PRODUCT FEATURES

Modern aesthetic and versatility with pull out spray rinse.

Two button rinse option, one actuating spray while depressed and the second keeps spray option active until deactivated or water is turned off.

The spout pivots offering the option of a full stream of water or spray.

Standard flow rate is 2.2gpm (8.3 L/min) and State of California requires a maximum of 1.8gpm(6.8 L/min). Also available in other flow options. Contact a sales associate for details.



## ODEON

Odeon One Hole Low Profile Kitchen Faucet with Pull-Out Spray  
and Metal Lever Handle

ODKM13

