WATERWORKS

FLYTE FLXT50

Flyte Deck Mounted Exposed Tub Filler with Handshower and Metal Lever Handles



SHOWN IN CHROME

INSPIRATION

Pure Modernism. Like minimalist works of art, the elegant proportions of these light, fluid elements bring sculptural reference to a room.

TECHNICAL DETAILS

ADA Compliance: Yes Adjustable versus Fixed Spray: Fixed Spray Deck Thickness Maximum: 1 5/16" Deck Thickness Minimum: 0" Diameter of Legs / Tubes: 1 9/16" **Escutcheon Primary Material: Brass** Fittings Hole Diameter: 1 1/4" Flow Restriction Options: 1.75, 1.5 Handle Spread Maximum: 10 7/16" Handle Spread Minimum: 10 7/16" Handle Turn Angle: Quarter Turn Handshower / Spray Hose Length: 59" Depth / Width: 13 5/16" Height: 9 1/16" Inlet Connection Size: 3/4" Inlet Connection Type: Male NPT Adapter Inlet Supply Spread Maximum: 5 7/8" Inlet Supply Spread Minimum: 5 7/8" Installation Type: Deck Mounted Integrated Diverter: N Integrated Spray: N Length: 11 1/4" Number of Handles: Three Number of Holes: Two Hole Pivot: N Primary Material: Brass Restricted Maximum Flow Rate: 2.0 gpm Spout Reach: 11 9/16" Spout Swivel: N Spray Included in Unit: N Suggested Application: Bath Valve Material: Ceramic Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

CODES & STANDARDS

Code # FLTU50:

PRODUCT FEATURES

Lever Handles

This item is stocked in a Chrome and Nickel finishes

Includes deck unions

Standard flow rate 2.0gpm. Also available in high efficient flow options. Contact your sales associate or call 1 (800) 899-6757 for details.

CERTIFICATIONS





PRODUCT (NOTES)

Includes deck unions.

FLYTE FLXT50

Flyte Deck Mounted Exposed Tub Filler with Handshower and Metal Lever Handles

