WATERWORKS

OMHS01 **OLYMPIA**

Olympia Handshower On Hook with Metal Handle



TECHNICAL DETAILS

ADA Compliance: Yes Adjustable versus Fixed Spray: Fixed Spray Diameter of Head: 2 1/2' Escutcheon Primary Material: Brass Fittings Hole Diameter: 1 1/4" Flow Restriction Options: 2.0, 1.75, 1.5, 0.92 Handshower / Spray Hose Length: 59" Depth / Width: 3 1/4" . Height: 8 3/4" Inlet Connection Size: 1/2" Inlet Connection Type: NPT Installation Type: Wall Mounted Integrated Diverter: N Interior / Exterior Application: Interior Only Length: 10 13/16" Pivot: N Primary Material: Brass Restricted Maximum Flow Rate: 2.5 gpm Suggested Application: Bath Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 25.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN OLYMPIA HANDSHOWER ON HOOK WITH METAL HANDLE OMHS01

INSPIRATION

Rooted in the industrial forms of the 1920's through 1940's, Olympia combines the straightforward functionality of Code # OMHS01: ASME A112.18.1 / CSA B125.1, State of MA, CEC the machine age, without the cold, hard edge. Olympia is proof that beauty and utility can coexist simply without ornamentation.

CODES & STANDARDS

PRODUCT FEATURES

Brass material is used for all trim and valve component parts.

The manufacturing process encompasses casting, turning, forging, hand-fitting and polishing. Unique details include the smooth, spherical knuckles on the cross handles and gentle curving spouts Standard flow rate is 2.5gpm (9.5 L/min). Also available in high efficient flow options. Contact your sales associate or call 1 (800) 899-6757 for details.









OLYMPIA OMHS01

Olympia Handshower On Hook with Metal Handle

