WATERWORKS

FLYTE FLXT30

Flyte Wall Mounted Exposed Tub Filler with Handshower and Metal Lever Handles



TECHNICAL DETAILS

ADA Compliance: Yes Adjustable versus Fixed Spray: Fixed Spray Escutcheon Primary Material: Brass Fittings Hole Diameter: 1 1/4" Flow Restriction Options: 1.75, 1.5 Handle Spread Maximum: 10 7/16" Handle Spread Minimum: 10 7/16" Handle Turn Angle: Quarter Turn Handshower / Spray Hose Length: 59" Depth / Width: 11 5/16" Height: 5" Inlet Connection Size: 3/4" Inlet Connection Type: Female NPT Inlet Supply Spread Maximum: 5 7/8" Inlet Supply Spread Minimum: 5 7/8" Installation Type: Wall Mounted Integrated Diverter: N Integrated Spray: N Length: 11 1/4" Number of Handles: Three Number of Holes: Two Hole Pivot: N Primary Material: Brass

Primary Material: Brass
Restricted Maximum Flow Rate: 2.0 gpm
Spout Reach: 11 1/4"
Spout Swivel: N
Spray Included in Unit: N
Suggested Application: Bath
Valve Material: Ceramic
Water Pressure Maximum: 85.0 psi
Water Pressure Recommended: 45.0 psi

SHOWN IN CHROME

INSPIRATION

Pure Modernism. Like minimalist works of art, the elegant proportions of these light, fluid elements bring sculptural reference to a room.

CODES & STANDARDS

Code # FLTU30:

PRODUCT FEATURES

Lever Handles

This item is stocked in a Chrome and Nickel finishes

Includes wall unions

Standard flow rate 2.0gpm. Also available in high efficient flow options. Contact your sales associate or call 1 (800) 899-6757 for details.

CERTIFICATIONS





PRODUCT (NOTES)

Includes wall unions.

FLYTE FLXT30

Flyte Wall Mounted Exposed Tub Filler with Handshower and Metal Lever Handles

