

UNIVERSAL

Universal Wall Mounted Shower Arm and Flange

UNSH35



SHOWN IN UNIVERSAL WALL MOUNTED SHOWER ARM AND FLANGE| UNSH35

TECHNICAL DETAILS

Escutcheon Primary Material: Brass
Fittings Hole Diameter: 1 1/8"
Depth / Width: 5 1/2"
Height: 3"
Inlet Connection Size: 1/2"
Inlet Connection Type: Female NPT
Installation Type: Wall Mounted
Integrated Diverter: N
Length: 2 3/16"
Primary Material: Brass
Suggested Application: Bath
Water Pressure Maximum: 85.0 psi
Water Pressure Minimum: 25.0 psi
Water Pressure Recommended: 45.0 psi

INSPIRATION

Our Universal collection features timeless designs complementing any of our Waterworks. With a wide range of product, from fittings to accessories, Universal adds exquisite proportion and balance to any environment.

CODES & STANDARDS

Code # WWSH35: ASME A112.18.1, CSA B125.1, IAPMO, State of MA, CEC

PRODUCT FEATURES

Customize your shower with a shower arm and flange suited to your spaces unique needs



PRODUCT (NOTES)

Shower Arm and Flange only; Head sold separately.

UNIVERSAL

UNSH35


Universal Wall Mounted Shower Arm and Flange



TOP VIEW SCALE: 3"=1'-0"



FRONT VIEW SCALE: 3"=1'-0"



SIDE VIEW SCALE: 3"=1'-0"