# WATERWORKS

ETOILE ETXS60

Etoile Exposed Thermostatic Shower Cage with 12" Rose



### **TECHNICAL DETAILS**

ADA Compliance: No
Adjustable Levelers / Feet: Y
Adjustable versus Fixed Spray: Fixed Spray
Assembly / Configuration: Completely Assembled
Diameter of Head: 12"
Escutcheon Primary Material: Brass
Fittings Hole Diameter: 1 5/8"
Handle Turn Angle: Quarter Turn
Index Color / Finish and Material: White Porcelain
Depth / Width: 46 1/2"
Height: 95"
Index Marking: Blank
Inlet Connection Size: 3/4"
Inlet Connection Type: Male NPT
Inlet Supply Spread Maximum: 9"

Inlet Supply Spread Maximum: 9" Inlet Supply Spread Minimum: 9" Installation Type: Wall Mounted Integrated Diverter: Y Length: 45"

Number of Handles: Four Pivot: Y Primary Material: Brass Suggested Application: Bath Valve Material: Brass

Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN ETOILE EXPOSED THERMOSTATIC SHOWER CAGE WITH 12" ROSE| ETXS60

### **INSPIRATION**

Defined elegance. Etoile has a European sophistication with a timeless sense of chic.

### **CODES & STANDARDS**

Code # ETSV60:

### **PRODUCT FEATURES**

Built in Anti-scald protection.

Features a swivel 12" shower rose.

Allows bather to adjust temperature and volume of shower rose, left and right water sprays, and tub filler.

 $The \ manufacturing \ process \ encompasses \ casting, \ turning, forging, hand-fitting \ and \ hand \ polishing.$ 

## PRODUCT (NOTES)

Valve Included

ETOILE ETXS60

Etoile Exposed Thermostatic Shower Cage with 12" Rose

