# WATERWORKS

EASTON EALS35

Easton Classic Gooseneck Three Hole Deck Mounted Lavatory Faucet with Oak Lever Handles



#### **TECHNICAL DETAILS**

Adjustable versus Fixed Spray: Fixed Spray
Deck Thickness Maximum: 32 mm
Deck Thickness Minimum: 0 mm
Drain Assembly Materials: Brass
Drain Depth Maximum: 70 mm
Drain Hole Diameter: 44 mm
Fittings Hole Diameter: 35 mm

Flow Restriction Options: 1.0 , 1.2 , 1.5 , 1.75, 2.2

Handle Spread Maximum: 305 mm Handle Spread Minimum: 203 mm Handle Turn Angle: Quarter Turn

Index Color / Finish and Material: White Porcelain

Depth / Width: 216 mm Drain Depth Minimum: 25 mm Height: 165 mm

Inlet Connection Size: 1/2"
Inlet Connection Type: Male with supply nut
Inlet Supply Spread Maximum: 305 mm
Inlet Supply Spread Minimum: 203 mm

Installation Type: Deck Mounted Length: 381 mm Number of Holes: Three Hole

Primary Material: Brass Spout Swivel: N Suggested Application: Bath Valve Material: Ceramic

Water Pressure Maximum: 6.0 bar Water Pressure Minimum: 1.5 bar Water Pressure Recommended: 3.0 bar

L SHOWN IN EASTON CLASSIC GOOSENECK THREE HOLE DECK MOUNTED LAVATORY FAUCET WITH OAK LEVER HANDLES|

### **INSPIRATION**

Drawing on Edwardian style, Easton is the most extensive Waterworks family; a range of moods and a selection of products from fittings to furniture.

# **CODES & STANDARDS**

Code # EALS35: CEC

# PRODUCT FEATURES

Standard flow rate is 2.2gpm (8.3 L/min) and State of California requires 1.2gpm(4.5 L/min). Also available in other flow options. Contact a sales associate for details.

### **CERTIFICATIONS**



## PRODUCT (NOTES)

Sold with European style drain; USA style drain sold separately for use with non-Waterworks sinks.

# EASTON EALS35

Easton Classic Gooseneck Three Hole Deck Mounted Lavatory Faucet with Oak Lever Handles

