

## ETOILE

ETLS69

Etoile Low Profile Two Hole Wall Mounted Lavatory Faucet (Curved Spout) with Cross Handles



SHOWN IN ETOILE LOW PROFILE TWO HOLE WALL MOUNTED LAVATORY FAUCET (CURVED SPOUT) WITH CROSS HANDLES | ETLS69

### TECHNICAL DETAILS

ADA Compliance: Yes  
 Adjustable Versus Fixed Spray: Fixed Spray  
 Depth/Width: 9"  
 Drain Assembly Materials: Brass  
 Drain Depth Maximum: 2 3/4"  
 Drain Depth Minimum: 1"  
 Drain Hole Diameter: 1 3/4"  
 Drain Style: Lift and Turn  
 Escutcheon Primary Material: Brass  
 Fittings Hole Diameter: 1 1/4"  
 Handle Spread Maximum: 7 7/8"  
 Handle Spread Minimum: 7 7/8"  
 Handle Turn Angle: Quarter Turn  
 Height: 2 7/8"  
 Index Color Finish And Material: White Porcelain  
 Index Marking: Hot/Cold  
 Inlet Connection Size: 1/2"  
 Inlet Connection Type: Female NPT  
 Inlet Supply Spread Maximum: 7 7/8"  
 Inlet Supply Spread Minimum: 7 7/8"  
 Installation Type: Wall Mounted  
 Length: 10 1/4"  
 Number Of Handles: Two  
 Number Of Holes: Two Hole  
 Primary Material: Brass  
 Restricted Maximum Flow Rate: 1.2 gpm  
 Spout Swivel: Y  
 Suggested Application: Bath  
 Valve Material: Ceramic  
 Water Pressure Maximum: 85.0 psi  
 Water Pressure Minimum: 20.0 psi  
 Water Pressure Recommended: 45.0 psi

### INSPIRATION

Defined elegance. Etoile has a European sophistication with a timeless sense of chic.

### CODES & STANDARDS

Code # ETLS69: Certified with IAPMO, NSF, CEC & State of MA. Complies with ASME A112.18.1 / CSA B125.1, ANSI 61 Sect. 9, ANSI A117.1 ADA, & ASTM E 1621-05.

### PRODUCT FEATURES

- Metal cross handles
- Includes European size lift and turn drain
- Features dew-drop designed cross handles and gracefully curved spout
- Stocked in Chrome, Nickel, Matte Nickel, and Unlacquered Brass
- Available in 1.2gpm (4.5L/min) flow rate

### CERTIFICATIONS



### PRODUCT (NOTES)

## ETOILE

ETLS69

Etoile Low Profile Two Hole Wall Mounted Lavatory Faucet  
(Curved Spout) with Cross Handles

