## WATERWORKS

EASTON EALS53

Easton Vintage Gooseneck Three Hole Deck Mounted Lavatory Faucet with White Porcelain Lever Handles



#### **TECHNICAL DETAILS**

Adjustable versus Fixed Spray: Fixed Spray Deck Thickness Maximum: 32 mm Deck Thickness Minimum: 0 mm **Drain Assembly Materials: Brass** Drain Depth Maximum: 70 mm Drain Hole Diameter: 44 mm Fittings Hole Diameter: 35 mm Handle Spread Maximum: 305 mm Handle Spread Minimum: 203 mm Handle Turn Angle: Quarter Turn Index Color / Finish and Material: White Porcelain Depth / Width: 216 mm Drain Depth Minimum: 25 mm Height: 165 mm Inlet Connection Size: 1/2" Inlet Connection Type: Male with supply nut Inlet Supply Spread Maximum: 305 mm Inlet Supply Spread Minimum: 203 mm Installation Type: Deck Mounted Length: 381 mm Number of Holes: Three Hole Primary Material: Brass Restricted Maximum Flow Rate: 4.5 liters/min Spout Swivel: N Suggested Application: Bath Valve Material: Ceramic Water Pressure Maximum: 6.0 bar Water Pressure Minimum: 1.5 bar Water Pressure Recommended: 3.0 bar

l Shown in Easton vintage gooseneck three hole deck mounted lavatory faucet with white porcelain

#### **INSPIRATION**

Drawing on Edwardian style, Easton is the most extensive Waterworks family; a range of moods and a selection of products from fittings to furniture.

### **CODES & STANDARDS**

Code # EALS53: CEC

#### **PRODUCT FEATURES**

Available in 1.2gpm (4.5L/min) flow rate

#### CERTIFICATIONS



#### PRODUCT (NOTES)

Sold with European style drain; USA style drain sold separately for use with non-Waterworks sinks.

# EASTON EALS53

Easton Vintage Gooseneck Three Hole Deck Mounted Lavatory Faucet with White Porcelain Lever Handles

