FLYTE FLXT70

Flyte Floor Mounted Exposed Tub Filler with Handshower and Metal Lever Handles



TECHNICAL DETAILS

Escutcheon Primary Material: Brass Fittings Hole Diameter: 1 3/8"

Flow Restriction Options: 2.0, 1.75, 1.5, 0.92

Handle Turn Angle: Quarter Turn Handshower Spray Hose Length: 59"

Height: 34 1/2"

Inlet Connection Size: 3/4"

Inlet Connection Type: Copper Sweat Inlet Supply Spread Maximum: 5 7/8" Inlet Supply Spread Minimum: 5 7/8"

Integrated Diverter: Y Length: 11 1/4"

Number Of Holes: Two Hole
Primary Material: Brass
Valve Material: Brass, Ceramic
Water Pressure Maximum: 80.0 psi
Water Pressure Minimum: 20.0 psi
Water Pressure Recommended: 45.0 psi

SHOWN IN FLYTE FLOOR MOUNTED EXPOSED TUB FILLER WITH HANDSHOWER AND METAL LEVER HANDLES | FLXT70

INSPIRATION

Pure Modernism. Like minimalist works of art, the elegant proportions of these light, fluid elements bring sculptural reference to a room.

CODES & STANDARDS

PRODUCT FEATURES

Lever Handles

This item is stocked in a Chrome and Nickel finishes.

Includes Floor Unions

Stocked in 2.0gpm (7.6 L/min) and 1.75gpm (6.6 L/min) for handshower. State of California requires 1.75gpm (6.6 L/min) to comply with their water conservation requirements. Other flow options are available to order, contact your sales associate or call 1 (800) 899-6757 for details.

CERTIFICATIONS





PRODUCT (NOTES)

WATERWORKS

FLYTE	FLXT70
Flyte Floor Mounted Exposed Tub Filler with Handshower and Metal Lever Handles	