WATERWORKS

EASTON EAXS32

Easton Classic Exposed Thermostatic System with 8" Shower Rose with Metal Lever Handle



TECHNICAL DETAILS

ADA Compliance: Yes

Adjustable versus Fixed Spray: Fixed Spray

Assembly / Configuration: Partially Assembled

Diameter of Head: 8"

Escutcheon Primary Material: Brass

Fittings Hole Diameter: 1 3/8"

Flow $\rm \bar{R}$ estriction Options: 2.5, 2.0, 1.75, 1.5, 0.92

Handshower / Spray Hose Length: 59"

Index Color / Finish and Material: Metal

Depth / Width: 23" Height: 55"

Index Marking: Blank

Inlet Connection Size: 3/4"

Inlet Connection Type: Compression

Inlet Supply Spread Maximum: 8 3/16"

Inlet Supply Spread Minimum: 8 1/16"

Installation Type: Wall Mounted

Integrated Diverter: N

Length: 10 1/4"

Number of Handles: One

Pivot: Y

Primary Material: Brass

Suggested Application: Bath

Valve Material: Brass

Water Pressure Maximum: 75.0 psi

Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

L SHOWN IN EASTON CLASSIC EXPOSED THERMOSTATIC SYSTEM WITH 8" SHOWER ROSE WITH METAL LEVER HANDLE

INSPIRATION

Drawing on Edwardian style, Easton is the most extensive Waterworks family; a range of moods and a selection of products from fittings to furniture.

CODES & STANDARDS

Code # EAXS32X: Certified with cUPC, NSF, IAPMO, CSA

PRODUCT FEATURES

Built in Anti-scald protection.

Optional handle materials include porcelain and semi-precious stones.

The pillowed propeller on the cross handle makes the product fit comfortably in the hand.

Add a handshower to this exposed system. Handshower not included.

Stocked in 2.5gpm (9.5 L/min) and 1.75gpm (6.6 L/min). State of California requires 1.75gpm (6.6 L/min) to comply with their water conservation requirements. Other flow options are available to order, contact your sales associate

CERTIFICATIONS







PRODUCT (NOTES)

Valve Included, Handshower Sold Separately

EASTON EAXS32

Easton Classic Exposed Thermostatic System with 8" Shower Rose with Metal Lever Handle

