

DISTRICT TILE



CYGNET



BUTTER



BIRCH



WHIPPET



PLATINUM



GRASSHOPPER



SEAWEED



FIG



PRIVET



MARIGOLD



SPARROW




HICKORY



BURNT SUGAR



LAGOON



INK



LICORICE

INSPIRATION

District Tile features transparent glazes characterized by pooling and a crackle surface in deep, rich colors. Assorted handmade or precise field sizes are complimented by moldings and trimmers—the architectural building blocks that create stunning interiors.

DESIGN KEYWORDS

- Rich
- Deep
- Artisinal
- Architectural building blocks

W A T E R W O R K S

COLOR PALETTE/VARIATION

COLOR	FINISH	VARIATION**
CYGNET	GLOSSY CRACKLE	1
BUTTER	GLOSSY CRACKLE	2-3
BIRCH	GLOSSY CRACKLE	2-3
WHIPPET	GLOSSY CRACKLE	2-3
PLATINUM	GLOSSY CRACKLE	2-3
GRASSHOPPER	GLOSSY CRACKLE	2-3
SEAWEED	GLOSSY CRACKLE	2-3
FIG	GLOSSY CRACKLE	3-4
PRIVET	GLOSSY CRACKLE	3-4
MARIGOLD	GLOSSY CRACKLE	2-3
SPARROW	GLOSSY CRACKLE	2-3
HICKORY	GLOSSY CRACKLE	2-3
BURNT SUGAR	GLOSSY CRACKLE	3-4
LAGOON	GLOSSY CRACKLE	2-3
INK	GLOSSY CRACKLE	3-4
LICORICE	GLOSSY CRACKLE	1

COLOR VARIATION INDICATED ABOVE IS FOR FIELD TILE ONLY
VARIATION FOR TRIMS/MOLDINGS CAN BE AS MUCH AS 4-5

**COLOR VARIATION

1. MINIMAL, IF ANY COLOR VARIATION
2. SLIGHT COLOR VARIATION CAN BE EXPECTED
3. A MEDIUM RANGE OF COLOR VARIATION IS TYPICAL; DARKER AND LIGHTER TONES ARE EVIDENT
4. CONSIDERABLE COLOR VARIATION IS TYPICAL; FROM DARKS TO LIGHTS AND SOME TONE CHANGES
5. EXTREME COLOR VARIATION CAN BE EXPECTED - THE RANGE IS OFTEN DIFFERING BUT COMPLIMENTARY COLOR VALUES, SUCH AS GREENS VARYING FROM YELLOWS TO BLUES

FIELD

All field tiles are available in handmade Classic or dust-pressed Modulus body style. All field tiles are also available in single or corner bullnose.

CLASSIC BODY	MODULUS BODY
CLASSIC FIELD TILE 1 X 4	MODULUS FIELD TILE 1 X 3 $\frac{3}{4}$
CLASSIC FIELD TILE 1 X 5 $\frac{1}{2}$	MODULUS FIELD TILE 1 X 5 $\frac{3}{4}$
CLASSIC FIELD TILE 1 $\frac{1}{4}$ X 2 $\frac{3}{4}$	MODULUS FIELD TILE 1 $\frac{1}{4}$ X 2 $\frac{3}{4}$
CLASSIC FIELD TILE 1 $\frac{1}{4}$ X 3 $\frac{3}{4}$	MODULUS FIELD TILE 1 $\frac{1}{4}$ X 3 $\frac{3}{4}$
CLASSIC FIELD TILE 1 $\frac{1}{4}$ X 5 $\frac{1}{2}$	MODULUS FIELD TILE 1 $\frac{1}{4}$ X 5 $\frac{3}{4}$
CLASSIC FIELD TILE 2 X 2	MODULUS FIELD TILE 1 $\frac{3}{4}$ X 1 $\frac{3}{4}$
CLASSIC FIELD TILE 2 X 5 $\frac{1}{2}$	MODULUS FIELD TILE 1 $\frac{3}{4}$ X 5 $\frac{3}{4}$
CLASSIC FIELD TILE 2 $\frac{3}{4}$ X 2 $\frac{3}{4}$	MODULUS FIELD TILE 2 $\frac{3}{4}$ X 2 $\frac{3}{4}$
CLASSIC FIELD TILE 2 $\frac{3}{4}$ X 5 $\frac{1}{2}$	MODULUS FIELD TILE 2 $\frac{3}{4}$ X 5 $\frac{3}{4}$
CLASSIC FIELD TILE 4 X 5 $\frac{1}{2}$	MODULUS FIELD TILE 3 $\frac{3}{4}$ X 5 $\frac{3}{4}$
CLASSIC FIELD TILE 3 $\frac{3}{4}$ X 3 $\frac{3}{4}$	MODULUS FIELD TILE 3 $\frac{3}{4}$ X 3 $\frac{3}{4}$
CLASSIC FIELD TILE 5 $\frac{1}{2}$ X 5 $\frac{1}{2}$	MODULUS FIELD TILE 5 $\frac{3}{4}$ X 5 $\frac{3}{4}$

TRIMMERS AND MOLDINGS

TRIMMERS	QUARTER ROUND 1 x 5 $\frac{3}{4}$ BEVEL COVE 1 x 5 $\frac{3}{4}$ QUARTER SQUARE $\frac{3}{8}$ x 5 $\frac{3}{4}$ QUARTER SQUARE COVE $\frac{3}{8}$ x 5 $\frac{3}{4}$ OUTSIDE BEVEL END 1 x 5 $\frac{3}{4}$
MOLDINGS	CROWN MOLDING 4 $\frac{1}{4}$ x 5 $\frac{3}{4}$ * BASE MOLDING 3 $\frac{7}{8}$ x 5 $\frac{3}{4}$ * *LEFT AND RIGHT STOPENDS AVAILABLE
RAILS	CROWN RAIL 2 x 5 $\frac{3}{4}$ * SQUARE RAIL 2 x 5 $\frac{3}{4}$ * DRIP EDGE RAIL 1 x 5 $\frac{3}{4}$ *LEFT AND RIGHT STOPENDS AVAILABLE
BASES	MUD BASE 3 $\frac{1}{4}$ x 5 $\frac{3}{4}$
LINERS	STANDARD LINER $\frac{1}{2}$ x 4 $\frac{1}{4}$ STANDARD LINER $\frac{1}{2}$ x 5 $\frac{3}{4}$ DOT LINER $\frac{3}{8}$ x 5 $\frac{3}{4}$ BEVEL LINER $\frac{3}{4}$ x 5 $\frac{3}{4}$ RIGHT AND LEFT GLAZED ENDS AVAILABLE UPTURNS, DOWNTURNS, INCORNER AND OUTCORNERS CAN BE AVAILABLE BY SPECIAL ORDER

APPLICATION AND USES

- Interior walls
- Can be used in a wet environment if properly installed and sealed (cannot be used for shower floors)

CUSTOM DESIGN

- Custom colors can be requested with a development fee of \$750
 - Minimum order quantity for custom color: 100 sq ft
 - Minimum lead-time for custom color: 14-16 weeks total (6-8 weeks for color development)
- Custom sizes, shapes and trimmers NOT AVAILABLE

FEATURES

- Made in the USA by local artisans
- Designed by Waterworks in collaboration with Roman & Williams
- Complimentary for modern, traditional and transitional design
- Rich colors with crackle glaze
- 2 body types:
 - CLASSIC: Hand formed, creating subtle variations
 - MODULUS: Dust-pressed to be uniform and precise
- Modulus tiles are designed to be modular so different sizes can be used in the same installation

THICKNESS

- Approximately ¼”

SUGGESTED GROUT LINES

- ⅛”

SAMPLES

- Recommended sampling minimum of 4 pieces for colors in the 3-4 variation range to clearly represent color variation (and color pooling at edges)
- Samples should be signed by client to represent acknowledgement of color variation and should be returned for color matching during production
- 3x3 carded samples of following colors will be stocked in support center and available for order. Samples of all other colors and trimmers can be special ordered from the supplier.

Cygnets
Birch
Whippet
Platinum
Privet
Burnt Sugar
Lagoon
Ink

ORDERING/LEAD TIME

- 8 week lead time
- Recommended overage is 10-15%
- Variation may vary from order to order and from showroom samples, boards and displays
- Requests to match previous orders can be made, but Waterworks cannot guarantee the color of new order will match prior order. Any such requests must be accompanied by purchase order # and sample from lot.

SHIPPING

FedEx Shipments

- All Field tile double boxed
- Trim and moldings packed in bubble wrap

Common Carrier (Truck) Shipments

- Orders palletized and shrink wrapped for safety
- One pallet can hold approximately 45 to 64 boxes weighing 1,500 to 2,300 pounds

INSTALLATION

WATERWORKS ASSUMES NO RESPONSIBILITY FOR INSTALLATION

- Tile should be installed by a licensed and experienced tile setter
- Refer to TCNA (Tile Council of North America) or ANSI standards for installation guidelines
- All tile must be inspected prior to installation
- Installation constitutes acceptance
- Grout joints should be 1/8"
- Seal tile prior to grouting
- Re-seal tile and grout after installation and maintain regularly
- Dry lay tile prior to installation to allow for blending of color variation

CARE & CLEANING

Clean glazed ceramic tile regularly with a non-abrasive, mild and PH neutral cleanser. Seal when water no longer beads on the joints and as needed; resealing is required.