

FLYTE

FLXT30

Flyte Wall Mounted Exposed Tub Filler with Handshower and Metal Lever Handles



SHOWN IN FLYTE WALL MOUNTED EXPOSED TUB FILLER WITH HANDSHOWER AND METAL LEVER HANDLES | FLXT30

TECHNICAL DETAILS

ADA Compliance: Yes
 Adjustable Versus Fixed Spray: Fixed Spray
 Depth/Width: 11 5/16"
 Escutcheon Primary Material: Brass
 Fittings Hole Diameter: 1 1/4"
 Flow Restriction Options: 2.0, 1.75, 1.5, 0.92
 Handle Spread Maximum: 10 7/16"
 Handle Spread Minimum: 10 7/16"
 Handle Turn Angle: Quarter Turn
 Handshower Spray Hose Length: 59"
 Height: 5"
 Inlet Connection Size: 3/4"
 Inlet Connection Type: Female NPT
 Inlet Supply Spread Maximum: 5 7/8"
 Inlet Supply Spread Minimum: 5 7/8"
 Installation Type: Wall Mounted
 Integrated Diverter: N
 Integrated Spray: N
 Length: 11 1/4"
 Number Of Handles: Three
 Number Of Holes: Two Hole
 Pivot: N
 Primary Material: Brass
 Spout Swivel: N
 Spray Included In Unit: N
 Suggested Application: Bath
 Valve Material: Ceramic
 Water Pressure Maximum: 85.0 psi
 Water Pressure Minimum: 20.0 psi
 Water Pressure Recommended: 45.0 psi

INSPIRATION

Pure Modernism. Like minimalist works of art, the elegant proportions of these light, fluid elements bring sculptural reference to a room.

CODES & STANDARDS

Code # FLTU30: State of MA

PRODUCT FEATURES

Lever Handles

This item is stocked in a Chrome and Nickel finishes.

Includes wall unions

Stocked in 2.0gpm (7.6 L/min) and 1.75gpm (6.6 L/min) for handshower. State of California requires 1.75gpm (6.6 L/min) to comply with their water conservation requirements. Other flow options are available to order, contact your sales associate or call 1 (800) 899-6757 for details.

CERTIFICATIONS



PRODUCT (NOTES)

Includes wall unions.

FLYTE

FLXT30

Flyte Wall Mounted Exposed Tub Filler with Handshower and Metal Lever Handles

