

LUDLOW

Ludlow Wall Mounted Tub Spout

LDS80



SHOWN IN LUDLOW WALL MOUNTED TUB SPOUT | LDS80

TECHNICAL DETAILS

ADA Compliance: Yes
Adjustable versus Fixed Spray: Fixed Spray
Escutcheon Primary Material: Brass
Fittings Hole Diameter: 1"
Depth / Width: 7 15/16"
Height: 3"
Inlet Connection Size: 1/2"
Inlet Connection Type: Female NPT
Installation Type: Wall Mounted
Integrated Diverter: N
Integrated Spray: N
Length: 2 1/2"
Number of Holes: One Hole
Pivot: N
Primary Material: Brass
Spout Swivel: N
Spray Included in Unit: N
Suggested Application: Bath
Water Pressure Maximum: 85.0 psi
Water Pressure Minimum: 20.0 psi
Water Pressure Recommended: 45.0 psi

INSPIRATION

A touch of classic Americana. Our fresh take on iconic industrial design has clean lines and dimensional details, including exposed screws and square plates.

CODES & STANDARDS

Code # LDS80Y: Complies with ASME A112.18.1/CSA B125.1, ADA and 0.25% Weighted Average Lead Content. Certified with IAPMO, cUPC, State of MA and WRAS.

PRODUCT FEATURES

Works seamlessly with Waterworks' thermostatic or diverter shower systems.
This item is stocked in a Chrome, Nickel and Unlacquered Brass finishes.




LUDLOW

Ludlow Wall Mounted Tub Spout


LDT580




TOP VIEW SCALE: 3"=1'-0"



ISO VIEW SCALE: 3"=1'-0"



FRONT VIEW SCALE: 3"=1'-0"



SIDE VIEW SCALE: 3"=1'-0"