

EASTON

EAXT24

Easton Classic Exposed Tub Filler, Black Porcelain Handshower and Lever Diverter



SHOWN IN EASTON CLASSIC EXPOSED TUB FILLER, BLACK PORCELAIN HANDSHOWER AND LEVER DIVERTER | EAXT24

TECHNICAL DETAILS

ADA Compliance: No
 Adjustable Versus Fixed Spray: Fixed Spray
 Depth/Width: 6 3/4"
 Flow Restriction Options: 2.5, 2.0, 1.75, 1.5, 0.92
 Handle Spread Maximum: 7 1/4"
 Handle Spread Minimum: 7 1/4"
 Handle Turn Angle: Quarter Turn
 Handshower Spray Hose Length: 59"
 Height: 15 1/2"
 Index Color Finish And Material: White Porcelain
 Inlet Connection Size: 3/4"
 Inlet Connection Type: Female Union Nut
 Inlet Supply Spread Maximum: 7 1/4"
 Inlet Supply Spread Minimum: 7 1/4"
 Installation Type: Wall or deck mounted
 Integrated Diverter: Y
 Length: 11"
 Primary Material: Brass
 Suggested Application: Bath
 Water Pressure Maximum: 75.0 psi
 Water Pressure Minimum: 20.0 psi
 Water Pressure Recommended: 45.0 psi

INSPIRATION

Drawing on Edwardian style, Easton is the most extensive Waterworks family; a range of moods and a selection of products from fittings to furniture.

CODES & STANDARDS

Code # EATU24-K: ASME A112.18.1, CSA B125, ASSE 1014, State of MA

PRODUCT FEATURES

Easton is our most comprehensive fittings family.

Easton has a clean-lined utilitarian profile, with a slightly elongated spout.

Unions sold separately - UNUN32 (Floor Union), EAUN16 (Deck Union) and EAUN18 (Wall Union)

Stocked in 2.5gpm (9.5 L/min) and 1.75gpm (6.6 L/min) for handshower. State of California requires 1.75gpm (6.6 L/min) to comply with their water conservation requirements. Other flow options are available to order, contact your sales associate or call 1 (800) 899-6757 for details.

CERTIFICATIONS

PRODUCT (NOTES)

EASTON

EAXT24

Easton Classic Exposed Tub Filler, Black Porcelain
Handshower and Lever Diverter

